

# Panasonic



DOMESTIC RANGE  
2024 / 2025



—ETHEREA—

heating & cooling solutions





## Panasonic domestic air to air heat pump

Panasonic has developed a range of products designed for you, better than ever before. Above all, it is also a range for air conditioning professionals, such as yourself, thanks to its broad range of products which are capable of conditioning rooms of all sizes – always with optimal efficiency and incomparable ease of installation.





|                                    |       |
|------------------------------------|-------|
| Highlighted features               | → 100 |
| Bringing nature's balance indoors  | → 102 |
| Etherea with nanoe™ X technology   | → 104 |
| Wall-mounted TZ super-compact      | → 106 |
| Super-compact units                | → 108 |
| Floor console                      | → 110 |
| Panasonic R2 rotary compressor     | → 112 |
| R22 Renewal                        | → 114 |
| Panasonic Comfort Cloud App        | → 116 |
| Voice Control                      | → 118 |
| Control and connectivity           | → 120 |
| Domestic air conditioner R32 range | → 122 |

### Wall-mounted

|                        |       |
|------------------------|-------|
| Etherea · R32          | → 124 |
| TZ super-compact · R32 | → 125 |
| BZ super-compact · R32 | → 126 |

### More options for your home

|                                     |       |
|-------------------------------------|-------|
| Floor console · R32                 | → 127 |
| Low static pressure hide-away · R32 | → 128 |
| Free Multi system                   | → 129 |
| Multi TZ system                     | → 132 |
| Compare solutions                   | → 133 |
| Feature comparison                  | → 134 |
| Features explained                  | → 136 |
| Accessories and control             | → 137 |

## Highlighted features

With innovative design, high efficiency and advanced technologies, such as the Panasonic Comfort Cloud App for smart control and nanoe™ X for indoor air quality improvement, the residential range has been designed with you and your clients in mind.





## Panasonic air conditioners provide more savings and more comfort.

We believe that going green shouldn't compromise on comfort.

Our super silent air conditioners guarantee clean indoor air for you and your family. For a cleaner living environment, the nanoe™ X helps improve the quality of the indoor air as well as your surroundings. Together, these breakthrough technologies embody Panasonic's Eco Clean Life Innovation - innovations that improve our environment whilst making life as comfortable as possible.

The iF Product Design Awards are among the most prestigious awards for product design excellence.

Winning the award thanks to its highly intelligent functionality, the Panasonic Floor console is the ideal air-conditioning system for domestic and commercial applications.



### Energy saving



#### Refrigerant R32.

Our heat pumps containing R32 refrigerant show a drastic reduction in the value of Global Warming Potential (GWP).



#### Exceptional seasonal cooling efficiency based on the ErP regulation.

10,50 SEER

Higher SEER ratings mean greater efficiency and year-round cooling savings!



#### Exceptional seasonal heating efficiency based on the ErP regulation.

6,20 SCOP

Higher SCOP ratings mean greater efficiency and year-round heating savings!



ECONAVI

#### Econavi. Sunlight sensor.

Sunlight Sensor technology can detect and reduce the waste of energy by optimising air conditioner operation according to room conditions. With just one touch of a button, you can save energy.



INVERTER+

#### Inverter Plus system.

Inverter Plus system classification highlights Panasonic's highest performing systems.



INVERTER

#### Inverter.

The Inverter range provides greater efficiency and comfort. Provides more precise temperature control, without highs and lows, and keeps the ambient temperature constant with lower energy consumption and a significant reduction in noise and vibration levels.



R2 ROTARY COMPRESSOR

#### Panasonic R2 rotary compressor.

Designed to withstand extreme conditions, it delivers high performance and efficiency.

### High performance and indoor air quality



nanoe X

#### nanoe™ X.

Technology with the benefits of hydroxyl radicals has the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise.



PM2.5 FILTER

#### PM2,5 filter.

This filter can capture airborne particulate matter (PM2,5), including hazardous pollutants, as well as house dust and pollen.



DUST COLLECTION FILTER

#### Dust collection filter.

This filter collects and retains particles suspended in the air, resulting in cleaner air in the room.



18 dB(A)

#### Super Quiet.

With Super Quiet technology our devices are quieter than a library (30 dB(A)).



INSIDE CLEANING ON DEMAND

#### Inside cleaning.

This function works to dry-off to inside of indoor unit with nanoe™ X. It can inhibit certain adhered bacteria, viruses and mould up to 99% efficiency.



HUMIDITY CONTROL MILD DRY

#### Mild Dry cooling.

Fine control helps prevent a rapid decrease in room humidity while maintaining the set temperature. Maintains an RH\* up to 10% higher than cooling operation (\*RH: Relative Humidity). Ideal when sleeping with the air conditioner on.



AEROWINGS

#### More comfort with Aerowings.

Panasonic's Aerowings feature incorporates two blades that concentrate the airflow to cool or heat in the shortest possible time by distributing the air evenly throughout the room.



STATIC PRESSURE UP TO 7 mmAq

#### Static pressure up to 7 mmAq.

Low static pressure hide-away with selectable static pressure up to 7 mmAq.



FILTER INCLUDED

#### Filter included.

Hide-away with filter included.



SUMMER HOUSE

#### Summer House.

This innovative function keeps the house at 8/10 or 8/15 °C to avoid freezing pipes during the winter. This function is beneficial for summer or weekend homes.



COOLING MODE

#### Down to -10 °C in cooling mode.

The air conditioner works in cooling mode when the outdoor temperature of -10 °C.



HEATING MODE

#### Down to -15 °C in heating mode.

The air conditioner works in heat pump mode when the outdoor temperature is as low as -15 °C.



R22 R410A R22 / R410A RENEWAL

#### R410A/R22 renewal.

The Panasonic renewal system allows good quality existing R410A or R22 pipe work to be re-used whilst installing high efficiency R32 systems.



5 YEARS COMPRESSOR WARRANTY

#### 5 Years compressor warranty.

We guarantee the outdoor unit compressors in the entire range for five years.

### High connectivity



INTEGRATION TO S-LINK

#### Domestic integration to S-Link - CZ-CAPRA1.

Can connect RAC range to S-Link. Full control is now possible.



WI-FI CONTROL

#### Wi-Fi control.

The Panasonic Comfort Cloud App allows users to conveniently manage and monitor Panasonic residential heat pumps from a mobile device, anytime, anywhere.



BMS CONNECTIVITY

#### BMS connectivity.

The communication port can be integrated into the indoor unit and provides easy connection to, and control of, your Panasonic air conditioner to your home or Building Management System.

# Bringing nature's balance indoors




## nanoe™ X, technology with the benefits of hydroxyl radicals.

Abundant in nature, hydroxyl radicals (also known as OH radicals) have the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise. nanoe™ X technology can bring these incredible benefits indoors so that hard surfaces, soft furnishings, and the indoor environment can be a cleaner and more pleasant place to be.



### What is unique about nanoe™ X?

#### Effective on fabrics and surfaces.



1 | At one billionth of a metre, nanoe™ X is much smaller than steam and can deeply penetrate cloth fabrics to deodorise.

#### Longer lifespan.




2 | Contained in tiny water particles, nanoe™ X has a long lifespan, which is about 600 seconds, to spread easily around the room.

#### Huge quantity.



3 | nanoe X Generator Mark 3 produces 48 trillion hydroxyl radicals per second. Greater amounts of hydroxyl radicals contained in nanoe™ X lead to higher performance on inhibition of pollutants.


#### Maintenance-free.



4 | No service and maintenance required. nanoe™ X is a filter free solution that does not require maintenance, as its atomisation electrode is enveloped with water during its generation process and it is made with Titanium.


### 7 effects of nanoe™ X – Panasonic unique technology

#### Deodorises




Odours

#### Capacity to inhibit 5 types of pollutants



Bacteria and viruses



Mould



Allergens



Pollen



Hazardous substances



Skin and hair

\* Refer to <https://aircon.panasonic.eu> for more details and validation data.

### First nanoe™ device was developed by Panasonic in 2003


#### Generator: nanoe™

2003

480 billion hydroxyl radicals/sec

#### Ion particle structure

Hydroxyl radicals




#### Generator: nanoe™ X

Mark 1 - 2016

4,8 trillion hydroxyl radicals/sec


10x times



Mark 2 - 2019

9,6 trillion hydroxyl radicals/sec


20x times



Mark 3 - 2022

48 trillion hydroxyl radicals/sec

100x times





## nanoe™ X, internationally-validated technology in testing facilities.

The effectiveness of nanoe™ X technology has been tested by 3rd party laboratories in Germany, France, Denmark, Japan and China.

The nanoe™ X performance varies depending on the room size, environment and usage and it may take several hours to reach the full effect. nanoe™ X is not medical device, local regulations on building design and sanitary recommendations must be followed. Test results conducted under controlled laboratory conditions. Performance of nanoe™ X might differ in real life environment.

|          | Tested contents |                                  | Generator | Result                                | Capacity         | Time  | Testing organisation  | Report No.        |
|----------|-----------------|----------------------------------|-----------|---------------------------------------|------------------|-------|---|-------------------|
| Airborne | Virus           | Influenza (H1N1)                 | Mark 2    | 98,3% inhibited                       | 30 m³            | 1,5 h | China Electronic Product Reliability and Environmental Testing Research Institute | J2003WT8888-00889 |
|          |                 | Bacteriophage ΦX174              | Mark 1    | 99,2% inhibited                       | Approx. 25 m³    | 6 h   | Kitasato Research Center for Environmental Science                                | 24_0300_1         |
|          | Bacteria        | Staphylococcus aureus            | Mark 1    | 99,7% inhibited                       | Approx. 25 m³    | 4 h   | Kitasato Research Center for Environmental Science                                | 24_0301_1         |
| Adhering | Virus           | SARS-CoV-2                       | Mark 1    | 91,4% inhibited                       | 6,7 m³           | 8 h   | Texcell (France)  | 1140-01 C3        |
|          |                 | SARS-CoV-2                       | Mark 1    | 99,9% inhibited                       | 45 L             | 2 h   | Texcell (France)  | 1140-01 A1        |
|          |                 | Bacteriophage ΦX174              | Mark 1    | 99,8% inhibited                       | Approx. 25 m³    | 8 h   | Japan Food Research Laboratories  | 13001265005-01    |
|          |                 | Xenotropic murine leukemia virus | Mark 1    | 99,999% inhibited                     | 45 L             | 6 h   | Charles River Biopharmaceutical Services GmbH                                     | —                 |
|          |                 | Coxsackie virus (CA16)           | Mark 2    | 99,9%inhibited                        | 30 m³            | 4 h   | China Electronic Product Reliability and Environmental Testing Research Institute | J2002WT8888-00439 |
|          |                 | Bacteriophage                    | Mark 3    | 98,81% inhibited                      | Approx. 139,3 m³ | 4 h   | SGS Inc   | SHES210901902584  |
|          |                 | MS2 Phage Virus                  | Mark 3    | 99,99% inhibited                      | Approx. 25 m³    | 2 h   | Shokukanken, Inc.   | 227131N           |
|          | Bacteria        | Staphylococcus aureus            | Mark 1    | 99,9% inhibited                       | 20 m³            | 8 h   | Danish Technological Institute  | 868988            |
|          | Pollen          | Cedar pollen                     | Mark 3    | 99%inhibited                          | Approx. 24 m³    | 12 h  | Panasonic Product Analysis Center   | H21YA017-1        |
|          |                 | Ambrosia pollen                  | Mark 1    | 99,4% inhibited                       | 20 m³            | 8 h   | Danish Technological Institute  | 868988            |
|          | Odours          | Cigarette smoke odour            | Mark 1    | Odour intensity reduced by 2,4 levels | Approx. 23 m³    | 0,2 h | Panasonic Product Analysis Center   | 4AA33-160615-N04  |
|          |                 |                                  | Mark 3    | Odour intensity reduced 1,7 levels    | Approx. 139,3 m³ | 0,5 h | SGS Inc   | SHES210901902478  |

### Licensed in VDI 6022

Certification of a HVAC system under VDI 6022 guarantees that the system fulfills the market's strictest hygiene requirements.



#### VDI 6022 – Part 5 <sup>1)</sup> Certification.

##### Avoidance of allergenic exposure.

Inhibits a wide range of harmful bacteria, viruses, mould, pollen and allergens.




#### VDI 6022 – Part 1 <sup>1)</sup> & 1.1 <sup>2)</sup> Certification.

##### Ventilation and indoor-air quality.

Panasonic nanoe™ X technology improving indoor air quality.

1) Certification mark only valid for nanoe X Generator Mark 3. 2) Certification mark only valid for nanoe X Generator Mark 2 and Mark 3.

## nanoe™ X: improving protection 24/7



Acts to clean your air, so that the indoor environment can be a cleaner and more pleasant place to be all day long. nanoe™ X works together with heating or cooling function when you are at home and can work independently when you are away. Give the air conditioning the strength to increase the protection at home with nanoe™ X technology and convenient control via the Panasonic Comfort Cloud App.

#### Cleans the air when you are away.


Leave the nanoe™ mode ON to inhibit certain pollutants and deodorise before you return home.

#### Improves your environment when you are at home.

Enjoy a cleaner, comfortable space with loved ones.



### Panasonic Heating & Cooling Solutions is incorporating nanoe™ technology in a wide range of equipment



**Wall-mounted Etherea.**  
**Built-in nanoe X Generator Mark 3.**



**Floor console.**  
**Built-in nanoe X Generator Mark 1.**



**Wall-mounted TZ super-compact.**  
**Built-in nanoe X Generator Mark 1.**

## Etherea with nanoe™ X technology


A smart solution to keep your home clean, comfortable and welcoming. The smart, Etherea comes with nanoe™ X technology with the benefits of hydroxyl radicals. With advanced control options, class-leading performance, a stylish design and intelligent features, Etherea is designed to make your home comfortable, clean and the ideal place to be.

—ETHEREA—

Available in 3 colors







Built-in  
nanoe X Generator Mark 3



BUILT-IN WI-FI

+ SEE PRODUCT SPECIFICATIONS

## 1 Air quality

- nanoe™ X technology with the benefits of hydroxyl radicals (Generator Mark 3)
- Acts to clean your air, so that the indoor environment can be a cleaner and more pleasant place to be all day long
- Cleaning and drying the indoor unit with nanoe™ X

## 2 Smart control

- Built-in Wi-Fi, now with easier and faster set-up
- Advanced smartphone control
- Compatible with Google Assistant and Amazon Alexa



## 3 High efficiency

- Top class energy efficiency up to A+++ in heating and cooling

## 4 Ultimate comfort

- Aerowings 2.0, end-to-end vanes enhance comfortable air flow
- Super Quiet ambient

## 5 Design


- Stylish, monolithic design available in graphite grey, silver and matt white
- Chassis and parts designed for easier installation and servicing
- High class, easy-to-use remote control with backlight



### nanoe™ X: Bringing nature's balance indoors

Etherea comes with nanoe X Generator Mark 3, the latest of the continuously evolving nanoe™ X technology. It has the largest amount of hydroxyl radicals in the history of nanoe™ - 48 trillion hydroxyl radicals per second, 100 times more than the traditional nanoe™. The increased number of hydroxyl radicals, which are the key to nanoe™ power, results in a higher level of performance.

Comparison of time required to inhibit 99% of cedar pollen.



### Technology for the ultimate comfort

#### Introducing the Aerowings 2.0 to the Etherea range.

Panasonic's Aerowings technology consists of two independent flexible vanes that concentrate air flow to heat or cool a room in the shortest time possible and helps distribute air evenly throughout a room.

Thanks to the larger sub vane (72 mm), which is more than doubled in size than other conventional designs, the ability to lift air flow has been further improved.



Aerowings 2.0 has a shower cooling feature which allows air flow to be concentrated evenly towards the ceiling to achieve comfortable cooling across a room, showering gently down into a room rather than one area subject to a continuous icy blast.




For heating, Aerowings 2.0 releases a concentrated air flow downwards to achieve an effect similar to floor heating the air, which rises and fills the room.



### Inside cleaning

The inside cleaning operation acts to clean the inside of indoor unit. It uses nanoe™ X technology that can inhibit certain adhered bacteria, viruses, and mould on the filter, evaporator and air outlet and filter up to 99%. Cross flow fan is coated to prevent dust adhered on its surfaces and can be effective against certain bacteria and mould.




Without coating:  
Adhered dust.



With anti-static coating:  
Maintain cleanliness.

Proven prevents dust adhered 62,5%\* compare with non-coating.



The amount of dust or mould may change depending on the usage frequency and environment.  
\* Based on Panasonic internal testing result.

## Wall-mounted TZ super-compact with nanoe™ X

Smart comfort and cleaner air in a compact unit.

TZ features nanoe™ X technology with the benefits of hydroxyl radicals for a cleaner and more comfortable indoor environment.







[+ SEE PRODUCT SPECIFICATIONS](#)

## 1 Air quality

- nanoe™ X technology with the benefits of hydroxyl radicals
- Acts to clean your air, so that the indoor environment can be a cleaner and more pleasant place to be all day long

## 2 Smart control

- Built-in Wi-Fi, now with easier and faster set-up
- Advanced smartphone control
- Compatible with Google Assistant and Amazon Alexa



## 3 Ultimate comfort

- Aerowings to control air draft direction
- Super Quiet ambient

## 4 Design

- Super-compact design, just 779 mm wide
- Chassis and parts designed for easier installation and servicing
- High class, easy-to-use remote control with backlight

### nanoe™ X: Bringing nature's balance indoors


Panasonic's nanoe™ X technology brings nature's detergent – hydroxyl radicals – indoors to help improve protection 24/7 against several types of pollutants can be inhibited such as certain types of bacteria, viruses, mould, allergens, pollen or hazardous substances.

The nanoe™ X performance varies depending on the room size, environment and usage and it may take several hours to reach the full effect (see page 103 for more detail). nanoe™ X is not medical device, local regulations on building design and sanitary recommendations must be followed.



### Super-compact design

The compact design of the indoor units have a width of just 779 mm. This allows for more installation possibilities, including the limited space above a door.




The easy-to-use remote controller features an ergonomic design with tapered rear housing for the most comfortable grip. The controller's intuitive design provides easy operation with five quick access keys for convenient use. The controller also has a minimalist design with the less frequently used keys concealed under a sliding cover.




### Aerowings

Panasonic's Aerowings feature incorporates two blades that concentrate air flow to cool you down in the shortest time possible. This also helps distribute cool air evenly throughout the room.



### Comfort that goes on and on with Shower Cooling.

When the Aerowings twin blades direct air towards the ceiling they create the Shower Cooling effect. This ensures cool air is evenly distributed throughout the room and you can stay comfortable without experiencing continuous direct cooling.



Panasonic Air Conditioners with Aerowings feature an indoor design with wider intake grille and super-high fan speed to produce bigger air flow.

## Wall-mounted indoor units, designed for simple installation and maintenance

The full range of wall-mounted indoor units has been carefully designed for simple, stress-free installation and ongoing maintenance.

\* Not applicable to VZ.







Feature available in Etherea,  
TZ, BZ

## 1 Simple installation

Thanks to advanced improvements, installation time has been dramatically decreased. The models have been designed to provide more stability and strength for neat installation, with newly built-in support and convenient access to the drain hose, cabling inserts and larger space for secure installation.

## 2 Easy maintenance

Meticulously designed for both installer and user benefit, the unit features an easy to remove front grille for convenient access to the interior. The inner workings of the unit have also been redesigned to make maintenance quicker and easier. Electronics and wiring components are now on just one side of the unit to simplify maintenance.



### 1. Stronger installation plate.

The models feature a stronger, solid installation plate that provides more stability and strength. For uneven surfaces, there are 2 additional screws to ensure a neat and secure installation.

#### Installation plate: Strong and solid.



Screw holder for uneven surface (screws not provided).



### 2. One-piece front grille.

The model comes with a one-piece front grille design to make servicing easier. First, open the intake grille and remove the screws. Next, slide the three slider locks and remove the front grille.

#### One-piece front grille: Easy removal.

Slider locks: Easy to unlock / lock.



### 3. Built-in support holder.

The model features a built-in support holder, making installation easier and providing convenience and workspace improvements.

#### Convenient installation and serviceability.




### 4. Easy access to drain hose and piping connection.


With larger piping space, pipes and insulations are securely and neatly hidden.

With the visible piping storage, pipes can easily be inspected for leaks without lifting the unit.

#### Piping storage: up to 15% larger (for TZ-ZKE).



#### Bigger working space.



### 5. Easy wire insertion and tightening.

The models have combined 2 wire inserts into 1, ensuring front visibility and convenience while inserting wires from the back.

#### Single tunnel: easy wire insert.




#### Bigger working space for wiring connection.



### 6. Easy removal of PCB.

PCB removal is achieved in just 4 easy steps. Simply remove the control board cover, disconnect all connectors from the indicator, disconnect all connectors and pull out the main PCB.

#### Simple steps for PCB removal.



### 7. Easy / hidden installation of the Wi-Fi adapter.

The latest model features a dedicated space for a network adapter. Easy to plug in, the guided wire slots allow for clear, easy installation and can be neatly tucked away - simple and out of sight!


\* Only for models without built-in network adapter.



### 8. Cross flow fan removal.

The models are carefully designed to make removal of cross flow fans easier compared to the previous models, saving valuable time.

#### Bigger diameter: up to Ø105 (for Z-ZKE).



## Floor console. Efficient comfort and clean air all year round

Floor console with nanoe™ X technology: outstanding efficiency A++, comfort (Super Quiet technology only 20 dB(A)) and better air quality combined in a breakthrough design.







The iF Product Design Awards are among the most prestigious awards for product design excellence. Winning the award thanks to its highly intelligent functionality, the Panasonic Floor console is the ideal air-conditioning system for domestic and commercial applications.

[+ SEE PRODUCT SPECIFICATIONS](#)

## 1 nanoe™ X: Bringing nature's balance indoors

Panasonic's nanoe™ X technology brings nature's detergent – hydroxyl radicals – indoors to help improve protection 24/7 against several types of pollutants can be inhibited such as certain types of bacteria, viruses, mould, allergens, pollen or hazardous substances.

The nanoe™ X performance varies depending on the room size, environment and usage and it may take several hours to reach the full effect (see page 103 for more detail). nanoe™ X is not medical device, local regulations on building design and sanitary recommendations must be followed.

## 2 Super Quiet operation

When the system reaches its set temperature, the unit will operate at only 20 dB(A). Creating a comfortable home is not only by temperature - a quiet atmosphere is also important.

## 3 Designed to follow the high European demands

Super Quiet operation, highly efficient and technology to help clean the air.

### Double air flow for improved comfort and temperature dispersion: through the top for an efficient operation



### Stylish infrared control

Enjoy innovative design at your fingertips with the stylish and sleek Backlit Sky Controller. Bigger screen and easier to use.




### Easy to integrate into your home

A breakthrough design that integrates perfectly with any style. We have carefully selected materials and processes to create an elegant design. Compact in size and with a stylish design, the floor console will easily integrate into your home's interior decoration. There are four options available:



### High energy efficiency class A++

The floor console brings the outdoor heat energy inside. Can provide heat inside even when it is -15 °C outside.



\* SCOP on heating mode for Floor console Type KIT-Z25-UFE and KIT-Z35-UFE compared with electrical heaters at +7 °C.


### The perfect solution for the replacement of old boiler heating systems



## Panasonic R2 rotary compressor

The secret is flexibility. Panasonic Inverter air conditioners have the flexibility to vary the rotation speed of the compressor. This allows it to use less energy to maintain the set temperature while also being able to cool the room quicker at start up.

So you can enjoy better savings on your electricity bills while maintaining cooling comfort.



R2 rotary compressors utilize rolling piston technology. The R2 compressor has been tested in extreme conditions: higher efficiency, single and dual piston, R32 / R410A refrigerant, compact size.




## Making the world a cooler place since 1978.

Panasonic rotary compressors for room air conditioners have been installed in the most demanding environments around the world. Designed to withstand extreme conditions, Panasonic Rotary delivers high performance, efficiency and reliable service, no matter where you are. Panasonic, the world's largest manufacturer of rotary compressors.

### Why is the Panasonic R2 rotary compressor so efficient?

1. High efficiency motor. The premium silicon steel motor meets industry efficiency requirements.
2. Improved lubrication of high volume oil pump. The extended, high volume oil pump in conjunction with a larger capacity oil reservoir provides superior lubrication.
3. Accumulator has larger refrigerant capacity. The larger accumulator accommodates generous refrigerant amounts needed in longer line length installations.



\* This image is for 5,0 / 7,1 kW.

## R2 compressor value

### About R2 compressor.

Built upon 36 years of compressor design and production experience, R2 is the next generation of rotary compressors for residential central air conditioning. The technology improvements, enhanced materials and simple design ensure R2 compressors are reliable, efficient and quiet. The R2 compressor delivers quality, comfort and peace of mind in homes around the world. Panasonic's Rotary Compressors have been life tested in some of the world's most demanding environments and the R2 design is the compressor of choice by contractors and homeowners in these challenging climates. For the high performance that home-owners demand, R2 rotary compressors are considered by the industry experts.

### Leading technology.

Used in over 80% of cooling solutions globally, rotary is the world's dominant residential air conditioning compression technology. Panasonic is the leading rotary and residential AC compressor manufacturer in the world, with over 200 million compressors produced.

### Benefits.

Central air conditioning delivered with a Panasonic R2 rotary compressor ensures a superior level of comfort at an economical cost.


## Inverter technology

### Great energy-saving performance. Reduces electricity consumption.

Panasonic Inverter air conditioners are designed to give you exceptional energy savings and performance. At the start up of an air conditioner's operation, a boost in power is required to reach the set temperature. After the set temperature is reached, less power is required to maintain it. The Panasonic Inverter air conditioner varies the rotation speed of the compressor. This provides a highly precise method of maintaining the set temperature.

### Constant comfort.

Precise temperature control with a wide power output range enables an Inverter air conditioner to meet different room occupancy levels – thus ensuring constant comfort.




\* Graph shows the 3,5 kW Inverter model's wide power output range during cooling.

### Quick comfort.


Panasonic Inverter air conditioners can operate with higher power during the start up period to cool the room 1,5 times faster and heat the room 4 times faster than non-Inverter models.

#### Comparison of cooling speed.



\* Comparison of 3,5 kW Inverter vs. non-Inverter. Outside room temperature: 35 °C; setting temperature: 25 °C.

#### Comparison of heating speed.



\* Comparison of 2,5 kW Inverter vs. non-Inverter. Outside room temperature: 2 °C; setting temperature: 25 °C.

## R22 Renewal. Panasonic standard units can be installed on existing R22 pipings

Change your old air conditioning system to a more efficient system!





An important drive to further reduce the potential damage to our ozone

- All Panasonic standard SKE, TKE and UKE units can be installed on existing R22 pipings
- No need for additional accessories (only pipe reductions)
- Approximately 30% energy savings compared to R22 units

### Panasonic is doing its part

We at Panasonic are also doing our part – recognising that all finances are under pressure at the moment. Panasonic has developed a clean and cost effective solution to enable this latest legislation to be introduced with as minimum an effect on businesses and cash reserves as possible.

The Panasonic renewal system allows good quality existing R22 pipe work to be re-used whilst installing new high efficiency R410A / R32 systems.

By bringing a simple solution to the problem Panasonic can renew all Split Systems and PACi systems; and depending upon certain restrictions we don't even limit the manufacturer's equipment we are replacing.

By installing a new high efficiency Panasonic R410A / R32 system you can benefit from around 30% running cost saving compared to the R22 system.

Yes...

1. Check the capacity of the system you wish to replace
2. Select from the Panasonic range the best system to replace it with
3. Follow the procedure detailed in the brochure and technical data

Simple...

R22 - The reduction of Chlorine critical for a cleaner future.



### Guidance on re-using existing R22 piping for a new R410A / R32 installation

#### 1. Precaution.

The existing R22 piping can be re-used for a R410A / R32 system installation if the following conditions are met and the piping are finally verified to be:

- Dry (no moisture remaining in the piping)
- Clean (no dust remaining in the piping)
- Tight (no refrigerant leak at the joining and piping)


#### 2. Conditions.

- Recover the refrigerant and oil.  
Operate "force cooling" according to the recommended operation time, regardless of the piping length. Single split: 10 min. Multi split: 30 min. After that, carry out "pump down" to recover the refrigerant and oil from the existing R22 system

\* Note: If pump down operation is not possible due to the malfunction of the system, flush and wash the existing piping to collect back the oil and dirt inside the system.

- Check the oil condition. If the oil contains dirt, wash the existing pipes
- Check the oil colour. After pump down, use a cotton bud to wipe the oil from the existing pipe. If the oil colour is higher than ASTM3, use a new pipe as re-use of old piping is not allowed
- Check pipe thickness. Make sure that the pipe thickness is more than 0,8 mm. If the thickness is less than 0,8 mm, use a new pipe
- Rework the flare for R410A / R32 connection. Do not reuse the old flare nuts

Deterioration criteria for refrigerant oil.



Make sure to use the new flare nuts attached to the R410A / R32 system.

\* Note: If the existing piping size is 1/4" (6,35 mm) and 1/2" (12,7 mm), and the new R410A / R32 system is 1/4" (6,35 mm) and 3/8" (9,52 mm), use a pipe reducer connected at indoor and outdoor unit.

#### 3. Applicable model.

Panasonic single split room air conditioner from CS/ CU-RE/UE/YE/XE/CE/NE/E\*NKE and PKE series onwards.  
Panasonic multi split room air conditioner from CU-2E/3E/4E/5PBE series onwards.

|       |                   | 1/4 (6,35)   |            |                         |
|-------|-------------------|--------------|------------|-------------------------|
|       |                   | Liquid       | Gas        |                         |
| Split | 16 / 20 / 25 / 35 | 1,6 - 3,5 kW | 3/8 (9,52) | 1/2 (12,70) 5/8 (15,88) |
|       | 42 / 50 / 60      | 4,2 - 6,0 kW | ×          | ✓                       |
|       | 71                | 6,8 - 7,5 kW | ×          | ×                       |
|       |                   |              | ×          | ✓                       |

✓ Standard piping connection with current piping length and refrigerant charge rules.

▲ This combinations is allowed respecting maximum piping length and refrigerant charged declared in model installed as new.

× This combinations is not allowed as it is out of piping diameter.

# Welcome to the connected world of Panasonic Comfort Cloud App

Whether you are at home or at work, the Panasonic Comfort Cloud App puts total control of your indoor air quality at your fingertips.



**nanoe™ X: improving protection 24/7.**



**Monitor energy consumption.**



**Remote control.**



**Pre-heat or cool spaces.**



**Weekly timer.**



**Error notifications.**



**Voice Control.**

## nanoe™ X: improving protection 24/7


Panasonic Comfort Cloud App allows you to see the nanoe™ X coverage in your space through a simulation.




Turn nanoe™ X on easily with "One-touch nanoe™ button" on the main screen.



Select the room shape and size and the unit installation position.



Observe the simulation of nanoe™ X concentration over time!




See page 102 for more detail.



## Monitor energy consumption.

Check the energy consumption of each individual unit across different time intervals by comparing the energy usage patterns to maximise energy savings and reduce the operating costs even more.



The Panasonic Comfort Cloud Application enables you to conveniently manage and monitor multiple air conditioning units for homes from just one mobile device. Also, energy monitoring is possible allowing opportunity to learn how to reduce the operating cost even more.

- Connectable up to 200 units\* with just 1 device
- Compatible for both residential and commercial applications


\* 10 different groups, with up to 20 units / per group.



## Easier setup with advanced built-in Wi-Fi


The advanced built-in Wi-Fi setup enables secured and easier connection to Panasonic Comfort Cloud App by scanning the QR code\*.

\*Feature available only in CS-XZ\*\*ZKEW-H, CS-XZ\*\*ZKEW, CS-MZ16ZKE, CS-Z\*\*ZKEW, CS-MTZ16ZKE and CS-TZ\*\*ZKEW.



Scan the QR code to enable easier Wi-Fi connectivity to the air conditioner.

## Requirements for connecting with Panasonic Comfort Cloud App



### Indoor unit with built-in Wi-Fi:

CS-XZ\*\*ZKEW-H, CS-XZ\*\*ZKEW, CS-MZ16ZKE, CS-Z\*\*ZKEW, CS-MTZ16ZKE, CS-TZ\*\*ZKEW and CS-Z\*\*YKEA.

Remark: indoor temperature display and some special functions are not available through the app for all models. Languages: Available in 20 European languages: Bulgarian, Croatian, Czech, Danish, Deutsch, English, Estonian, Finnish, French, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Slovenian, Spanish, Swedish, Turkish and Lithuanian.



### Indoor unit with optional CZ-TACG1 Wi-Fi adapter:

CS-BZ\*\*ZKE, CZ-UZ\*\*ZKE, CS-MZ20UFEA, CS-Z\*\*UFEAW, CS-MZ20UD3EA and CS-Z\*\*UD3EAW

### Indoor unit with optional CZ-CAPWFC1 Wi-Fi adapter or CONEX remote controller:

S-M20PY3E and S-\*\*PY3E.

## Download free app: Panasonic Comfort Cloud App.

Other hardware requirements: Router and Internet (purchase and subscribe separately). Built-in Wi-Fi in certain models or with optional adaptor CZ-TACG1 connected to port CN-CNT. Panasonic Cloud Server is designed, operated and managed by Panasonic.



## Voice Control. Words do more than actions

Boundless control and hands-free help to access all the features of your air-to-air heat pump. Maximising your comfort is now a breeze with our connected air conditioners using the Panasonic Comfort Cloud App and voice control.



### Seamless set up in 3 simple steps

Set up your Panasonic Comfort Cloud App.



Set up your Google Nest Mini or Amazon Echo devices and app.



Link your Google Nest Mini or Amazon Echo with Panasonic Comfort Cloud App.



#### Compatible devices as of January 2023:

1. Android™ 7.1 or above
2. iOS 13.6 or above

#### Please note:


- This is not a definitive list of all compatible devices, other similar devices which use supported Operating Systems should also work either via dedicated apps. Please note that user experience may vary slightly depending on hardware and software combination
- Google, Android, Google Play and Google Home are trademarks of Google LLC.
- Google Assistant is not available in certain languages and countries
- Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates
- Availability of Voice Assistant services varies depending on country and language
- Google Assistant and Alexa are compatible with the models shown in pages 122 and 123.



### Turn ON / OFF air conditioner

#### Convenient control for blissful rest.

Turn ON / OFF AC with ease when preparing a comfortable space for your little ones.



### Adjust temperature

#### Easy control for uninterrupted quality time.

Adjust AC temperature to your comfort with a simple voice command.



### Change mode

#### Extra help when you have a hectic day.

Conveniently change your AC operation mode to cool / heat / auto when your hands are full.



### Check current status

#### Hands-free comfort for the whole family.

Easy access for the elderly to check current AC operation status and adjust AC settings.



### Get multiple things done with your voice


Simplify your day with your personalised routine by grouping individual actions.

#### Schedule your routine with your voice.


With the routine function, you can customise voice commands and control multiple voice-controlled devices including our network-enabled air conditioners to help you with your personalised routine.

Find out more (Amazon):  
<https://www.techhive.com/article/3327501/how-to-use-alexa-routines.html>

#### Example of morning routine.



#### Example of night routine.



### Voice Control with Network-Enabled air conditioners

| Functions        |  | When you are home |               | When away from home         |
|------------------|--|-------------------|---------------|-----------------------------|
|                  |  | Remote control    | Voice Control | Panasonic Comfort Cloud App |
| Smart control    | Power ON / OFF                               | ✓                 | ✓             | ✓                           |
|                  | Control multiple units in 1 location         | —                 | —             | ✓                           |
|                  | Control multiple units in multiple locations | —                 | —             | ✓                           |
|                  | Set up and manage routines                   | —                 | ✓             | —                           |
| Smart comfort    | Cooling mode                                 | ✓                 | ✓             | ✓                           |
|                  | Heating mode                                 | ✓                 | ✓             | ✓                           |
|                  | Auto mode                                    | ✓                 | ✓             | ✓                           |
|                  | nanoe™ X mode                                | ✓                 | —             | ✓                           |
|                  | Inside cleaning                              | ✓                 | —             | ✓                           |
|                  | Summer House mode                            | ✓                 | —             | ✓                           |
|                  | Pre-cool                                     | —                 | —             | ✓                           |
|                  | Change temperature                           | ✓                 | ✓             | ✓                           |
| Smart efficiency | Analyse energy usage patterns                | —                 | —             | ✓                           |
|                  | Compare historical usage                     | —                 | —             | ✓                           |
|                  | Receive error notifications                  | —                 | —             | ✓                           |
| Smart assist     | Assign multiple users                        | —                 | ✓             | ✓                           |
|                  | Check power ON / OFF                         | ✓                 | ✓             | ✓                           |
|                  | Check temperature settings                   | ✓                 | ✓             | ✓                           |
|                  | Check room temperature                       | ✓                 | ✓             | ✓                           |



## Control and connectivity

Panasonic offers its customers cutting-edge technology, specially designed to ensure our air conditioning systems deliver even higher performance.

You can properly manage the air conditioning and perform comprehensive monitoring and control, with all of the features the remote controller provides at home, from anywhere in the world thanks to the internet applications Panasonic has created for you.



### Wi-Fi adapter for smart control via Panasonic Comfort Cloud App

#### **CZ-TACG1. Wi-Fi adaptor (optional)\*.**

- Optional Wi-Fi adaptor for domestic range
- Compact size for easy installation
- Available for built-in or exposed installation depending on model type

\* Functionality varies depending on models. Please contact your local dealers for compatible models.

#### **Specifications.**

- |                                     |  |
|-------------------------------------|--|
| · Input voltage: DC 12 V            | · Interface: 1 x Wireless LAN              |
| · Power consumption: Maximum 660 mW | · Wireless LAN standard: IEEE 802,11 b/g/n |
| · Size (HxWxD): 66x36x12 mm         | · Frequency range: 2,4GHz band             |
| · Mass: Approx. 85 g                | · Encryption: WPA2-PSK (TKIP/AES)          |



## Domestic integration to S-Link

### CZ-CAPRA1


Can connect RAC range to S-Link. Full control is now possible.

#### Integrates any unit in big system control.

- YKEA server room integration <sup>1)</sup>
- Small offices with domestic indoors
- Tender for refurbishment (old system Domestic and VRF in one installation)
- Centralized Control Systems: 64 indoor units
- Intelligent controller / Web Server: 256 indoor units
- Panasonic AC Smart Cloud

- Basic operation items: ON / OFF, Mode select, Temperature setting, Fan speed, Flap setting, Remote control prohibit
- External input: ON / OFF control signal, Abnormal stop signal
- External output for Relay <sup>2)</sup>: Operation status (ON / OFF), Alarm status output

1) When duty rotation using the remote controller is set up, CZ-CAPRA1 cannot be connected.  
2) Because current CN-CNT connector can not provide the power for external output relay, additional 12 V DC power supply for external relay is necessary.



## Control by BMS

### PAW-AC-KNX-1i (Intesis), PAW-AC-MBS-1 (Intesis), PAW-AC-BAC-1 <sup>1)</sup> (Intesis), PAW-AZAC-KNX-1 (Airzone), PAW-AZAC-MBS-1 (Airzone) and PAW-AZAC-BAC-1 (Airzone).

Great flexibility for integration into your KNX, Modbus and BACnet projects allows fully bi-directional monitoring and control of all the functioning parameters.

- Quick Installation
- External power not required
- Direct connection to the unit via CN-CNT connector
- Bidirectional control
- Unit can be controller simultaneously by remote controller and the gateway

1) This interface allows a complete and natural integration of Panasonic air conditioners into either BACnet IP or MS/TP networks. Is a BTL certified device. \* For specific functionality list of each gateway, please check the user's manual.

## Easy connectivity








CN-CNT port easy to access in all indoor units, without dismantling the unit to reach the connector. Can easier connect: Wireless accessory / KNX / Modbus / BACnet / CZ-TACG1 / CZ-CAPRA1 to integrate to PACi control.




| Model name    | Interface  |
|---------------|--|
| CZ-TACG1      | Wi-Fi adapter for smart control via Panasonic Comfort Cloud App                                |
| CZ-CAPRA1     | RAC interface adapter for integration into S-Link, plus external input and alarm/status output |
| PAW-AC-KNX-1i | KNX interface. Can be used with all models which have a CN-CNT connector (Intesis)             |
| PAW-AC-MBS-1  | Modbus interface. Can be used with all models which have a CN-CNT connector (Intesis)          |
| PAW-AC-BAC-1  | BACnet interface. Can be used with all models which have a CN-CNT connector (Intesis)          |

| Model name     | Interface   |
|----------------|---|
| PAW-AZAC-KNX-1 | KNX interface. Can be used with all models which have a CN-CNT connector (Airzone)    |
| PAW-AZAC-MBS-1 | Modbus interface. Can be used with all models which have a CN-CNT connector (Airzone) |
| PAW-AZAC-BAC-1 | BACnet interface. Can be used with all models which have a CN-CNT connector (Airzone) |
| PAW-AC-DIO     | This interface can be used with all models which have a CN-RMT connector              |



















# Domestic air conditioner R32 range

| Page                                       | Single split units  | 2,0 kW                     | 2,5 kW                     | 3,5 kW                     | 4,2 kW                     | 5,0 kW                     | 6,0 kW                     | 7,1 kW                    |
|--|---|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|---------------------------|
| <b>Wall-mounted Etherea · R32</b>          |   |                            |                            |                            |                            |                            |                            |                           |
| P. 124                                     |    | CS-XZ20ZKEW-H<br>CU-Z20ZKE | CS-XZ25ZKEW-H<br>CU-Z25ZKE | CS-XZ35ZKEW-H<br>CU-Z35ZKE | CS-XZ42ZKEW-H<br>CU-Z42ZKE |                            |                            |                           |
|  |    | CS-XZ20ZKEW<br>CU-Z20ZKE   | CS-XZ25ZKEW<br>CU-Z25ZKE   | CS-XZ35ZKEW<br>CU-Z35ZKE   |                            | CS-XZ50ZKEW<br>CU-Z50ZKE   |                            |                           |
|  |    | CS-Z20ZKEW<br>CU-Z20ZKE    | CS-Z25ZKEW<br>CU-Z25ZKE    | CS-Z35ZKEW<br>CU-Z35ZKE    | CS-Z42ZKEW<br>CU-Z42ZKE    | CS-Z50ZKEW<br>CU-Z50ZKE    |                            | CS-Z71ZKEW<br>CU-Z71ZKE   |
| <b>Wall-mounted TZ super-compact · R32</b> |   |                            |                            |                            |                            |                            |                            |                           |
| P. 125                                     |    | CS-TZ20ZKEW<br>CU-TZ20ZKE  | CS-TZ25ZKEW<br>CU-TZ25ZKE  | CS-TZ35ZKEW<br>CU-TZ35ZKE  | CS-TZ42ZKEW<br>CU-TZ42ZKE  | CS-TZ50ZKEW<br>CU-TZ50ZKE  | CS-TZ60ZKEW<br>CU-TZ60ZKE  | CS-TZ71ZKEW<br>CU-TZ71ZKE |
| <b>Wall-mounted BZ super-compact · R32</b> |   |                            |                            |                            |                            |                            |                            |                           |
| P. 126                                     |    |                            | CS-BZ25ZKE<br>CU-BZ25ZKE   | CS-BZ35ZKE<br>CU-BZ35ZKE   |                            | CS-BZ50ZKE<br>CU-BZ50ZKE   | CS-BZ60ZKE<br>CU-BZ60ZKE   |                           |
| <b>Floor console · R32</b>                 |   |                            |                            |                            |                            |                            |                            |                           |
| P. 127                                     |  |                            | CS-Z25UFEAW<br>CU-Z25UBEA  | CS-Z35UFEAW<br>CU-Z35UBEA  |                            | CS-Z50UFEAW<br>CU-Z50UBEA  |                            |                           |
| <b>Low static pressure hide-away · R32</b> |   |                            |                            |                            |                            |                            |                            |                           |
| P. 128                                     |  |                            | CS-Z25UD3EAW<br>CU-Z25UBEA | CS-Z35UD3EAW<br>CU-Z35UBEA |                            | CS-Z50UD3EAW<br>CU-Z50UBEA | CS-Z60UD3EAW<br>CU-Z60UBEA |                           |

Try Panasonic's augmented reality tool, the AR Heat Pump Viewer.





| Page                          | Free Multi indoors  | 1,6 kW  | 2,0 kW  | 2,5 kW  | 3,5 kW  | 4,2 kW  | 5,0 kW  | 6,0 kW  | 7,1 kW  |
|-------------------------------|---|---|---|---|---|---|---|---|---|
| Wall-mounted Etherea          |   |   |   |   |   |   |   |   |   |
| P. 131                        |    | CS-XZ20ZKEW-H CS-XZ25ZKEW-H CS-XZ35ZKEW-H CS-XZ42ZKEW-H                             |   |   |   |   |   |   |   |
|                               |    | CS-XZ20ZKEW CS-XZ25ZKEW CS-XZ35ZKEW CS-XZ50ZKEW                                     |   |   |   |   |   |   |   |
|                               |    | CS-MZ16ZKE  | CS-Z20ZKEW  | CS-Z25ZKEW  | CS-Z35ZKEW  | CS-Z42ZKEW  | CS-Z50ZKEW  | CS-Z71ZKEW  |   |
| Wall-mounted TZ super-compact |   |   |   |   |   |   |   |   |   |
| P. 131                        |    | CS-MTZ16ZKE   | CS-TZ20ZKEW   | CS-TZ25ZKEW   | CS-TZ35ZKEW   | CS-TZ42ZKEW   | CS-TZ50ZKEW   | CS-TZ60ZKEW   | CS-TZ71ZKEW   |
| Floor console                 |   |   |   |   |   |   |   |   |   |
| P. 131                        |    | CS-MZ20UFEA CS-Z25UFEAW CS-Z35UFEAW CS-Z50UFEAW                                     |   |   |   |   |   |   |   |
| 4 Way 60x60 cassette          |   |   |   |   |   |   |   |   |   |
| P. 131                        |  | S-M20PY3E<br>CZ-KPY4  | S-25PY3E<br>CZ-KPY4   | S-36PY3E<br>CZ-KPY4   | S-50PY3E<br>CZ-KPY4   |   | S-60PY3E<br>CZ-KPY4   |   |   |
| Low static pressure hide-away |   |   |   |   |   |   |   |   |   |
| P. 131                        |  | CS-MZ20UD3EA CS-Z25UD3EAW CS-Z35UD3EAW CS-Z50UD3EAW CS-Z60UD3EAW                    |   |   |   |   |   |   |   |
| Page                          | Free Multi outdoors   | 3,2 ~ 6,0 kW  | 3,2 ~ 6,0 kW  | 3,2 ~ 7,7 kW  | 4,5 ~ 9,5 kW  | 4,5 ~ 11,2 kW   | 4,5 ~ 11,5 kW   | 4,5 ~ 14,7 kW   | 4,5 ~ 18,3 kW   |
| P. 130                        | Outdoor units Free Multi system Z · R32   |  |  |  |  |   |  |  |  |
|                               |   | CU-2Z35TBE  | CU-2Z41TBE  | CU-2Z50TBE  | CU-3Z52TBE  | CU-3Z68TBE  | CU-4Z68TBE  | CU-4Z80TBE  | CU-5Z90TBE  |
| Page                          | Multi wall TZ outdoors  | 3,2 ~ 6,0 kW  | 3,2 ~ 7,7 kW  |   |   | 4,5 ~ 9,5 kW  |   |   |   |
| P. 132                        | Outdoor units Multi TZ for wall TZ indoors · R32                                    |  |  |   |   |  |   |   |   |
|                               |   | CU-2TZ41TBE   | CU-2TZ50TBE   |   |   | CU-3TZ52TBE   |   |   |   |

Configure your multi split system in a few steps using our online tool and see all possible combinations.



## Wall-mounted Etherea · R32

- nanoe™ X technology to improve protection 24/7
- Stylish, monolithic design available in graphite grey, silver and matt white
- Improved SEER / SCOP for top class energy efficiency
- Aerowings 2.0 for the ultimate comfort
- Easy-to-use remote controller
- Built-in Wi-Fi for smart control via Panasonic Comfort Cloud App
- Compatible with Google Assistant and Amazon Alexa
- Chassis and parts designed for easier installation



| Graphite grey                           |                       |                     | 2,0 kW             | 2,5 kW             | 3,5 kW             | 4,2 kW             | —                  | —                   |
|---|-----------------------|---------------------|--------------------|--------------------|--------------------|--------------------|--------------------|---------------------|
| Silver                                  |                       |                     | 2,0 kW             | 2,5 kW             | 3,5 kW             | —                  | 5,0 kW             | —                   |
| Matt white                              |                       |                     | 2,0 kW             | 2,5 kW             | 3,5 kW             | 4,2 kW             | 5,0 kW             | 7,1 kW              |
| Cooling capacity                        | Nominal (Min - Max)   | kW                  | 2,05 [0,75 - 2,65] | 2,50 [0,85 - 3,50] | 3,50 [0,85 - 4,20] | 4,20 [0,85 - 5,00] | 5,00 [0,98 - 6,00] | 7,10 [0,98 - 8,50]  |
| EER <sup>1)</sup>                       | Nominal (Min - Max)   | W/W                 | 4,66 [4,69 - 4,02] | 4,90 [5,00 - 3,89] | 4,27 [4,25 - 3,62] | 3,39 [3,62 - 3,18] | 3,68 [3,92 - 3,16] | 3,24 [2,33 - 2,83]  |
| SEER <sup>2)</sup>                      |                       |                     | 8,70 A+++          | 9,50 A+++          | 9,50 A+++          | 7,10 A++           | 8,50 A+++          | 6,50 A++            |
| Pdesign (cooling)                       |                       | kW                  | 2,1                | 2,5                | 3,5                | 4,2                | 5,0                | 7,1                 |
| Input power                             | Nominal (Min - Max)   | kW                  | 0,44 [0,16 - 0,66] | 0,51 [0,17 - 0,90] | 0,82 [0,20 - 1,16] | 1,24 [0,24 - 1,57] | 1,36 [0,25 - 1,90] | 2,19 [0,42 - 3,00]  |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a               | 84                 | 92                 | 129                | 207                | 206                | 382                 |
| Heating capacity                        | Nominal (Min - Max)   | kW                  | 2,80 [0,75 - 4,00] | 3,40 [0,80 - 4,80] | 4,00 [0,80 - 5,50] | 5,30 [0,80 - 6,80] | 5,80 [0,98 - 8,00] | 8,20 [0,98 - 10,20] |
| Heating capacity at -7 °C               |                       | kW                  | 2,38               | 2,8                | 3,2                | 4,11               | 4,8                | 6,31                |
| COP <sup>1)</sup>                       | Nominal (Min - Max)   | W/W                 | 4,67 [4,69 - 4,26] | 4,86 [5,00 - 4,07] | 4,55 [4,44 - 3,77] | 3,73 [4,21 - 3,66] | 4,14 [4,26 - 3,35] | 3,73 [2,45 - 3,31]  |
| SCOP <sup>2)</sup>                      |                       |                     | 4,80 A++           | 5,20 A+++          | 5,20 A+++          | 4,30 A+            | 4,80 A++           | 4,20 A+             |
| Pdesign at -10 °C                       |                       | kW                  | 2,4                | 2,6                | 2,9                | 3,6                | 4,2                | 5,5                 |
| Input power                             | Nominal (Min - Max)   | kW                  | 0,60 [0,16 - 0,94] | 0,70 [0,16 - 1,18] | 0,88 [0,18 - 1,46] | 1,42 [0,19 - 1,86] | 1,40 [0,23 - 2,39] | 2,20 [0,40 - 3,08]  |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a               | 700                | 700                | 781                | 1172               | 1225               | 1833                |
| Indoor unit graphite grey               |                       |                     | CS-XZ20ZKEW-H      | CS-XZ25ZKEW-H      | CS-XZ35ZKEW-H      | CS-Z42ZKEW-H       | —                  | —                   |
| Indoor unit silver                      |                       |                     | CS-XZ20ZKEW        | CS-XZ25ZKEW        | CS-XZ35ZKEW        | —                  | CS-XZ50ZKEW        | —                   |
| Indoor unit matt white                  |                       |                     | CS-Z20ZKEW         | CS-Z25ZKEW         | CS-Z35ZKEW         | CS-Z42ZKEW         | CS-Z50ZKEW         | CS-Z71ZKEW          |
| Power supply                            | V                     |                     | 230                | 230                | 230                | 230                | 230                | 230                 |
| Recommended fuse                        | A                     |                     | 16                 | 16                 | 16                 | 16                 | 16                 | 20                  |
| Connection indoor / outdoor             | mm <sup>2</sup>       |                     | 4x1,5              | 4x1,5              | 4x1,5              | 4x1,5              | 4x2,5              | 4x2,5               |
| Air flow                                | Cool / Heat           | m <sup>3</sup> /min | 10,4/11,9          | 12,4/13,0          | 12,7/14,4          | 14,5/15,4          | 17,4/19,1          | 19,0/19,9           |
| Moisture removal volume                 | L/h                   |                     | 1,3                | 1,5                | 2                  | 2,4                | 2,8                | 4,1                 |
| Sound pressure <sup>4)</sup>            | Cool (Hi / Lo / Q-Lo) | dB(A)               | 35/24/19           | 39/25/19           | 42/28/19           | 43/31/25           | 44/37/30           | 47/38/30            |
|   | Heat (Hi / Lo / Q-Lo) | dB(A)               | 36/25/19           | 39/27/19           | 43/33/19           | 43/35/29           | 44/37/30           | 47/38/30            |
| Dimension                               | H x W x D             | mm                  | 295 x 870 x 229    | 295 x 870 x 229    | 295 x 870 x 229    | 295 x 870 x 229    | 295 x 1040 x 244   | 295 x 1040 x 244    |
| Net weight                              | kg                    |                     | 10                 | 10                 | 11                 | 10                 | 12                 | 13                  |
| nanoe X Generator                       |                       |                     | Mark 3             | Mark 3             | Mark 3             | Mark 3             | Mark 3             | Mark 3              |
| Outdoor unit                            |                       |                     | CU-Z20ZKE          | CU-Z25ZKE          | CU-Z35ZKE          | CU-Z42ZKE          | CU-Z50ZKE          | CU-Z71ZKE           |
| Air flow                                | Cool / Heat           | m <sup>3</sup> /min | 26,5/25,7          | 28,7/26,5          | 29,8/29,8          | 29,8/30,9          | 39,8/36,9          | 44,7/45,8           |
| Sound pressure <sup>4)</sup>            | Cool / Heat (Hi)      | dB(A)               | 45/46              | 46/47              | 48/50              | 49/51              | 47/47              | 52/54               |
| Dimension <sup>5)</sup>                 | H x W x D             | mm                  | 542 x 780 x 289    | 542 x 780 x 289    | 542 x 780 x 289    | 542 x 780 x 289    | 695 x 875 x 320    | 695 x 875 x 320     |
| Net weight                              | kg                    |                     | 27                 | 27                 | 31                 | 31                 | 40                 | 45                  |
| Piping diameter                         | Liquid                | Inch (mm)           | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]          |
|   | Gas                   | Inch (mm)           | 3/8 [9,52]         | 3/8 [9,52]         | 3/8 [9,52]         | 1/2 [12,70]        | 1/2 [12,70]        | 5/8 [15,88]         |
| Pipe length range                       | m                     |                     | 3 ~ 15             | 3 ~ 15             | 3 ~ 15             | 3 ~ 15             | 3 ~ 30             | 3 ~ 30              |
| Elevation difference (in / out)         | m                     |                     | 15                 | 15                 | 15                 | 15                 | 15                 | 20                  |
| Pre-charged pipe length                 | m                     |                     | 7,5                | 7,5                | 7,5                | 7,5                | 7,5                | 10                  |
| Additional gas amount                   | g/m                   |                     | 10                 | 10                 | 10                 | 10                 | 15                 | 25                  |
| Refrigerant (R32) / CO <sub>2</sub> Eq. | kg / T                |                     | 0,70/0,47          | 0,70/0,47          | 0,81/0,55          | 0,83/0,56          | 1,13/0,76          | 1,35/0,91           |
| Operating range                         | Cool Min ~ Max        | °C                  | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43           |
|   | Heat Min ~ Max        | °C                  | -20 ~ +24          | -20 ~ +24          | -20 ~ +24          | -20 ~ +24          | -20 ~ +24          | -20 ~ +24           |

1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the indoor unit shows the value measured at a position of 1 m in front of the main body and 0,8 m below the unit. For outdoor unit 1 m in front and 1 m in rear side of main body. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 5) Add 70 mm for piping port.

## Accessories

**CZ-CAPRA1** RAC interface adapter for integration into S-Link

## Accessories

**CZ-RD517C** Wired remote controller for wall-mounted and floor console



SEER and SCOP: For KIT-\*\*25-ZKE and KIT-\*\*35-ZKE. SUPER QUIET: For KIT-\*\*20-ZKE, KIT-\*\*25-ZKE and KIT-\*\*35-ZKE. INTERNET CONTROL: Built-in Wi-Fi.

## Wall-mounted TZ super-compact · R32

- nanoe™ X technology to improve protection 24/7
- Compact and elegant design with only 779 mm wide
- Built-in Wi-Fi for smart control via Panasonic Comfort Cloud App
- Compatible with Google Assistant and Amazon Alexa
- Easy-to-use remote controller
- Aerowings to control air draft direction



|   |                       |                     | 2,0 kW             | 2,5 kW             | 3,5 kW             | 4,2 kW             | 5,0 kW             | 6,0 kW             | 7,1 kW              |
|---|-----------------------|---------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|---------------------|
| Cooling capacity                        | Nominal (Min - Max)   | kW                  | 2,00 [0,75 - 2,50] | 2,50 [0,85 - 3,00] | 3,50 [0,85 - 4,00] | 4,20 [0,85 - 4,60] | 5,00 [0,98 - 5,60] | 6,00 [0,98 - 6,60] | 7,10 [0,98 - 8,40]  |
| EER <sup>1)</sup>                       | Nominal (Min - Max)   | W/W                 | 4,08 [4,17 - 3,91] | 3,85 [4,05 - 3,41] | 3,57 [3,62 - 3,33] | 3,36 [3,62 - 2,80] | 3,13 [3,92 - 2,96] | 3,24 [3,92 - 2,87] | 3,23 [2,33 - 2,80]  |
| SEER <sup>2)</sup>                      |                       |                     | 7,00 A++           | 7,10 A++           | 6,80 A++           | 6,40 A++           | 6,90 A++           | 6,80 A++           | 6,20 A++            |
| Pdesign [cooling]                       |                       | kW                  | 2,0                | 2,5                | 3,5                | 4,2                | 5,0                | 6,0                | 7,1                 |
| Input power                             | Nominal (Min - Max)   | kW                  | 0,49 [0,18 - 0,64] | 0,65 [0,21 - 0,88] | 0,98 [0,24 - 1,20] | 1,25 [0,24 - 1,64] | 1,60 [0,25 - 1,89] | 1,85 [0,25 - 2,30] | 2,20 [0,42 - 3,00]  |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a               | 100                | 123                | 180                | 230                | 254                | 309                | 401                 |
| Heating capacity                        | Nominal (Min - Max)   | kW                  | 2,70 [0,70 - 3,60] | 3,30 [0,80 - 4,10] | 4,00 [0,80 - 5,10] | 5,00 [0,80 - 6,80] | 5,80 [0,98 - 7,50] | 7,00 [0,98 - 8,20] | 8,20 [0,98 - 10,20] |
| Heating capacity at -7 °C               |                       | kW                  | 2,14               | 2,70               | 3,30               | 3,90               | 4,62               | 4,90               | 6,31                |
| COP <sup>1)</sup>                       | Nominal (Min - Max)   | W/W                 | 4,15 [4,24 - 3,53] | 4,18 [4,21 - 3,66] | 4,04 [4,10 - 3,70] | 3,73 [4,10 - 3,33] | 3,41 [4,67 - 3,26] | 3,72 [4,67 - 3,57] | 3,71 [2,45 - 3,29]  |
| SCOP <sup>2)</sup>                      |                       |                     | 4,60 A++           | 4,60 A++           | 4,60 A++           | 4,10 A+            | 4,50 A+            | 4,30 A+            | 4,10 A+             |
| Pdesign at -10 °C                       |                       | kW                  | 2,1                | 2,4                | 2,8                | 3,6                | 4,0                | 4,4                | 5,5                 |
| Input power                             | Nominal (Min - Max)   | kW                  | 0,65 [0,17 - 1,02] | 0,79 [0,19 - 1,12] | 0,99 [0,20 - 1,38] | 1,34 [0,20 - 2,04] | 1,70 [0,21 - 2,30] | 1,88 [0,21 - 2,30] | 2,21 [0,40 - 3,10]  |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a               | 639                | 730                | 852                | 1229               | 1244               | 1433               | 1878                |
| <b>Indoor unit</b>                      |                       |                     | <b>CS-TZ20ZKEW</b> | <b>CS-TZ25ZKEW</b> | <b>CS-TZ35ZKEW</b> | <b>CS-TZ42ZKEW</b> | <b>CS-TZ50ZKEW</b> | <b>CS-TZ60ZKEW</b> | <b>CS-TZ71ZKEW</b>  |
| Power supply                            | V                     |                     | 230                | 230                | 230                | 230                | 230                | 230                | 230                 |
| Recommended fuse                        | A                     |                     | 16                 | 16                 | 16                 | 16                 | 16                 | 20                 | 20                  |
| Connection indoor / outdoor             | mm <sup>2</sup>       |                     | 4x1,5              | 4x1,5              | 4x1,5              | 4x1,5              | 4x2,5              | 4x2,5              | 4x2,5               |
| Air flow                                | Cool / Heat           | m <sup>3</sup> /min | 9,9/10,4           | 11,0/11,5          | 11,8/12,3          | 12,5/13,2          | 12,5/13,2          | 18,4/19,4          | 19,0/19,9           |
| Moisture removal volume                 | L/h                   |                     | 1,3                | 1,5                | 2                  | 2,4                | 2,8                | 3,3                | 4,1                 |
| Sound pressure <sup>4)</sup>            | Cool (Hi / Lo / Q-Lo) | dB(A)               | 37/25/20           | 40/26/20           | 42/30/20           | 44/31/25           | 44/37/33           | 45/37/34           | 47/38/35            |
|   | Heat (Hi / Lo / Q-Lo) | dB(A)               | 38/26/22           | 40/27/22           | 42/33/22           | 44/35/28           | 44/37/33           | 45/37/34           | 47/38/35            |
| Dimension                               | H x W x D             | mm                  | 290 x 779 x 209    | 290 x 779 x 209    | 290 x 779 x 209    | 290 x 779 x 209    | 290 x 779 x 209    | 295 x 1040 x 244   | 295 x 1040 x 244    |
| Net weight                              | kg                    |                     | 8                  | 8                  | 8                  | 8                  | 8                  | 12                 | 13                  |
| nanoe X Generator                       |                       |                     | Mark 1             | Mark 1             | Mark 1             | Mark 1             | Mark 1             | Mark 1             | Mark 1              |
| <b>Outdoor unit</b>                     |                       |                     | <b>CU-TZ20ZKE</b>  | <b>CU-TZ25ZKE</b>  | <b>CU-TZ35ZKE</b>  | <b>CU-TZ42ZKE</b>  | <b>CU-TZ50ZKE</b>  | <b>CU-TZ60ZKE</b>  | <b>CU-TZ71ZKE</b>   |
| Air flow                                | Cool / Heat           | m <sup>3</sup> /min | 29,7/29,7          | 30,0/28,9          | 28,7/29,7          | 31,0/31,3          | 32,7/32,7          | 34,4/35,6          | 44,7/45,8           |
| Sound pressure <sup>4)</sup>            | Cool / Heat (Hi)      | dB(A)               | 46/47              | 47/48              | 48/50              | 49/51              | 48/49              | 49/51              | 52/54               |
| Dimension <sup>5)</sup>                 | H x W x D             | mm                  | 542 x 780 x 289    | 542 x 780 x 289    | 542 x 780 x 289    | 542 x 780 x 289    | 619 x 824 x 299    | 619 x 824 x 299    | 695 x 875 x 320     |
| Net weight                              | kg                    |                     | 24                 | 25                 | 29                 | 31                 | 35                 | 35                 | 45                  |
| Piping diameter                         | Liquid                | Inch (mm)           | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]          |
|   | Gas                   | Inch (mm)           | 3/8 [9,52]         | 3/8 [9,52]         | 3/8 [9,52]         | 1/2 [12,70]        | 1/2 [12,70]        | 1/2 [12,70]        | 5/8 [15,88]         |
| Pipe length range                       | m                     |                     | 3 ~ 15             | 3 ~ 15             | 3 ~ 15             | 3 ~ 15             | 3 ~ 20             | 3 ~ 30             | 3 ~ 30              |
| Elevation difference (in / out)         | m                     |                     | 15                 | 15                 | 15                 | 15                 | 15                 | 15                 | 20                  |
| Pre-charged pipe length                 | m                     |                     | 7,5                | 7,5                | 7,5                | 7,5                | 10                 | 10                 | 10                  |
| Additional gas amount                   | g/m                   |                     | 10                 | 10                 | 10                 | 10                 | 15                 | 15                 | 25                  |
| Refrigerant (R32) / CO <sub>2</sub> Eq. | kg / T                |                     | 0,52/0,35          | 0,61/0,41          | 0,67/0,45          | 0,79/0,53          | 1,07/0,72          | 1,22/0,82          | 1,35/0,91           |
| Operating range                         | Cool Min ~ Max        | °C                  | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          | -10 ~ +43           |
|   | Heat Min ~ Max        | °C                  | -15 ~ +24          | -15 ~ +24          | -15 ~ +24          | -15 ~ +24          | -15 ~ +24          | -15 ~ +24          | -15 ~ +24           |

1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the indoor unit shows the value measured of a position of 1 m in front of the main body and 0,8 m below the unit. For outdoor unit 1 m in front and 1 m in rear side of main body. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 5) Add 70 mm for piping port.

## Accessories

**CZ-CAPRA1** RAC interface adapter for integration into S-Link

## Accessories

**CZ-RD517C** Wired remote controller for wall-mounted and floor console



SEER and SCOP: For KIT-TZ25-ZKE. SUPER QUIET: For KIT-TZ20-ZKE, KIT-TZ25-ZKE and KIT-TZ35-ZKE. INTERNET CONTROL: Built-in Wi-Fi.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites [www.aircon.panasonic.eu](http://www.aircon.panasonic.eu) or [www.ptc.panasonic.eu](http://www.ptc.panasonic.eu).



1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the indoor unit shows the value measured of a position of 1 m in front of the main body and 0,8 m below the unit. For outdoor unit 1 m in front and 1 m in rear side of main body. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 5) Add 70 mm for piping port.

| Accessories |  |
|-------------|--|
| CZ-RD517C   | Wired remote controller for wall-mounted and floor console |



## Floor console • R32

- nanoe™ X technology to improve protection 24/7 (nanoe X Generator Mark 1)
- Stylish Sky remote controller
- A breakthrough design that integrates perfectly with the most modern environments
- High energy efficiency class A++ SEER and A++ SCOP
- Optional internet and voice control



|   |                       |           | 2,5 kW             | 3,5 kW             | 5,0 kW             |
|---|-----------------------|-----------|--------------------|--------------------|--------------------|
| Cooling capacity                        | Nominal (Min - Max)   | kW        | 2,50 [0,85 - 3,40] | 3,50 [0,85 - 3,80] | 5,00 [0,90 - 5,70] |
| EER <sup>1)</sup>                       | Nominal (Min - Max)   | W/W       | 4,81 [3,54 - 3,78] | 4,07 [3,54 - 3,73] | 3,60 [3,53 - 3,15] |
| <b>SEER <sup>2)</sup></b>               |                       |           | <b>7,90 A++</b>    | <b>8,10 A++</b>    | <b>6,70 A++</b>    |
| Pdesign (cooling)                       |                       | kW        | 2,50               | 3,50               | 5,00               |
| Input power                             | Nominal (Min - Max)   | kW        | 0,52 [0,24 - 0,90] | 0,86 [0,24 - 1,02] | 1,39 [0,26 - 1,81] |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a     | 111                | 151                | 261                |
| Heating capacity                        | Nominal (Min - Max)   | kW        | 3,40 [0,85 - 5,00] | 4,30 [0,85 - 6,00] | 5,80 [0,90 - 8,10] |
| Heating capacity at -7 °C               |                       | kW        | 2,88               | 3,37               | 5,03               |
| COP <sup>1)</sup>                       | Nominal (Min - Max)   | W/W       | 4,47 [3,54 - 3,70] | 3,98 [3,54 - 3,43] | 3,74 [3,46 - 3,12] |
| <b>SCOP <sup>2)</sup></b>               |                       |           | <b>4,60 A++</b>    | <b>4,60 A++</b>    | <b>4,30 A+</b>     |
| Pdesign at -10 °C                       |                       | kW        | 2,70               | 3,20               | 4,40               |
| Input power                             | Nominal (Min - Max)   | kW        | 0,76 [0,24 - 1,35] | 1,08 [0,24 - 1,75] | 1,55 [0,26 - 2,60] |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a     | 822                | 974                | 1433               |
| <b>Indoor unit</b>                      |                       |           | <b>CS-Z25UFEAW</b> | <b>CS-Z35UFEAW</b> | <b>CS-Z50UFEAW</b> |
| Air flow                                | Cool / Heat           | m³/min    | 9,6 / 9,9          | 9,9 / 10,1         | 11,6 / 13,2        |
| Moisture removal volume                 |                       | L/h       | 1,5                | 2,0                | 2,8                |
| Sound pressure <sup>4)</sup>            | Cool (Hi / Lo / Q-Lo) | dB(A)     | 38 / 25 / 20       | 39 / 26 / 20       | 44 / 31 / 27       |
|   | Heat (Hi / Lo / Q-Lo) | dB(A)     | 38 / 25 / 19       | 39 / 26 / 19       | 46 / 33 / 29       |
| Dimension                               | H x W x D             | mm        | 600 x 750 x 207    | 600 x 750 x 207    | 600 x 750 x 207    |
| Net weight                              |                       | kg        | 13                 | 13                 | 13                 |
| nanoe X Generator                       |                       |           | Mark 1             | Mark 1             | Mark 1             |
| <b>Outdoor unit</b>                     |                       |           | <b>CU-Z25UBEA</b>  | <b>CU-Z35UBEA</b>  | <b>CU-Z50UBEA</b>  |
| Power supply                            |                       | V         | 230                | 230                | 230                |
| Recommended fuse                        |                       | A         | 16                 | 16                 | 16                 |
| Connection indoor / outdoor             |                       | mm²       | 4x1,5              | 4x1,5              | 4x1,5              |
| Air flow                                | Cool / Heat           | m³/min    | 28,7 / 27,2        | 34,3 / 33,5        | 39,7 / 38,6        |
| Sound pressure <sup>4)</sup>            | Cool / Heat (Hi)      | dB(A)     | 46 / 47            | 48 / 48            | 48 / 48            |
| Dimension <sup>5)</sup>                 | H x W x D             | mm        | 542 x 780 x 289    | 619 x 824 x 299    | 695 x 875 x 320    |
| Net weight                              |                       | kg        | 33                 | 35                 | 43                 |
| Piping diameter                         | Liquid                | Inch (mm) | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         |
|   | Gas                   | Inch (mm) | 3/8 [9,52]         | 3/8 [9,52]         | 1/2 [12,70]        |
| Pipe length range                       |                       | m         | 3 ~ 20             | 3 ~ 20             | 3 ~ 30             |
| Elevation difference (in / out)         |                       | m         | 15                 | 15                 | 20                 |
| Pre-charged pipe length                 |                       | m         | 7,5                | 7,5                | 7,5                |
| Additional gas amount                   |                       | g/m       | 10                 | 10                 | 15                 |
| Refrigerant (R32) / CO <sub>2</sub> Eq. |                       | kg / T    | 0,88 / 0,594       | 0,93 / 0,628       | 1,13 / 0,763       |
| Operating range                         | Cool Min ~ Max        | °C        | -10 ~ +43          | -10 ~ +43          | -10 ~ +43          |
|   | Heat Min ~ Max        | °C        | -15 ~ +24          | -15 ~ +24          | -15 ~ +24          |

1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the units shows the value measured of a position 1 m in front of the main body and 1 m above floor. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 5) Add 70 mm for piping port.

## Accessories

|                  |   |
|------------------|---|
| <b>CZ-TACG1</b>  | Wi-Fi adapter for smart control via Panasonic Comfort Cloud App |
| <b>CZ-CAPRA1</b> | RAC interface adapter for integration into S-Link               |

## Accessories

|                  |  |
|------------------|--|
| <b>CZ-RD517C</b> | Wired remote controller for wall-mounted and floor console |
|------------------|--|



SEER and SCOP: For KIT-Z35-UFE. SUPER QUIET: For KIT-Z25-UFE and KIT-Z35-UFE. INTERNET CONTROL: Optional. IF DESIGN AWARD 2019: Floor console awarded with the prestigious IF Design Award 2019.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites [www.aircon.panasonic.eu](http://www.aircon.panasonic.eu) or [www.ptc.panasonic.eu](http://www.ptc.panasonic.eu).

## Low static pressure hide-away · R32

- Duct type can be controlled by KNX and Modbus
- Eco mode for 20% energy saving
- Extremely compact indoor units without losing static pressure (only 200 mm high)
- Weekly timer, 42 settings per week
- Easy check mode for failure detection
- Drain pump included



Optional wireless control kit. CZ-RL511D


[+ MORE DUCT TYPE SOLUTIONS IN PACI SECTION](#)

|   |                       |           | 2,5 kW              | 3,5 kW              | 5,0 kW              | 6,0 kW              |
|---|-----------------------|-----------|---------------------|---------------------|---------------------|---------------------|
| Cooling capacity                        | Nominal (Min - Max)   | kW        | 2,50 [0,85 - 3,20]  | 3,50 [0,85 - 4,00]  | 5,10 [0,90 - 5,70]  | 6,00 [0,90 - 6,50]  |
| EER <sup>1)</sup>                       | Nominal (Min - Max)   | W/W       | 4,31 [3,54 - 3,76]  | 3,85 [3,54 - 3,36]  | 3,27 [3,53 - 3,20]  | 2,94 [3,53 - 2,83]  |
| <b>SEER <sup>2)</sup></b>               |                       |           | <b>5,90 A+</b>      | <b>5,80 A+</b>      | <b>5,90 A+</b>      | <b>5,60 A+</b>      |
| Pdesign (cooling)                       |                       | kW        | 2,50                | 3,50                | 5,10                | 6,00                |
| Input power                             | Nominal (Min - Max)   | kW        | 0,58 [0,24 - 0,85]  | 0,91 [0,24 - 1,19]  | 1,56 [0,26 - 1,78]  | 2,04 [0,26 - 2,30]  |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a     | 148                 | 211                 | 303                 | 375                 |
| Heating capacity                        | Nominal (Min - Max)   | kW        | 3,20 [0,85 - 4,60]  | 4,20 [0,85 - 5,10]  | 6,10 [0,90 - 7,20]  | 7,00 [0,90 - 8,00]  |
| Heating capacity at -7 °C               |                       | kW        | 2,60                | 3,00                | 4,50                | 5,10                |
| COP <sup>1)</sup>                       | Nominal (Min - Max)   | W/W       | 4,00 [3,70 - 3,68]  | 3,82 [3,70 - 3,59]  | 3,35 [3,46 - 3,27]  | 3,24 [3,46 - 3,08]  |
| <b>SCOP <sup>2)</sup></b>               |                       |           | <b>4,20 A+</b>      | <b>4,10 A+</b>      | <b>4,10 A+</b>      | <b>4,10 A+</b>      |
| Pdesign at -10 °C                       |                       | kW        | 2,60                | 2,80                | 4,00                | 4,60                |
| Input power                             | Nominal (Min - Max)   | kW        | 0,80 [0,23 - 1,25]  | 1,10 [0,23 - 1,42]  | 1,82 [0,26 - 2,20]  | 2,16 [0,26 - 2,60]  |
| Annual energy consumption <sup>3)</sup> |                       | kWh/a     | 867                 | 956                 | 1366                | 1571                |
| <b>Indoor unit</b>                      |                       |           | <b>CS-Z25UD3EAW</b> | <b>CS-Z35UD3EAW</b> | <b>CS-Z50UD3EAW</b> | <b>CS-Z60UD3EAW</b> |
| External static pressure <sup>4)</sup>  | Min - Max             | Pa        | 15 - 45             | 15 - 45             | 15 - 50             | 15 - 50             |
| Air flow                                | Cool / Heat           | m³/min    | 10,5 / 10,5         | 11,2 / 11,2         | 15,3 / 15,3         | 15,7 / 15,7         |
| Moisture removal volume                 |                       | L/h       | 1,5                 | 2,0                 | 2,8                 | 3,3                 |
| Sound pressure <sup>5)</sup>            | Cool (Hi / Lo / Q-Lo) | dB(A)     | 33 / 27 / 24        | 33 / 27 / 24        | 39 / 29 / 26        | 41 / 30 / 27        |
|   | Heat (Hi / Lo / Q-Lo) | dB(A)     | 35 / 27 / 24        | 35 / 27 / 24        | 39 / 30 / 27        | 41 / 32 / 29        |
| Dimension                               | H x W x D             | mm        | 200 x 750 x 640     | 200 x 750 x 640     | 200 x 750 x 640     | 200 x 750 x 640     |
| Net weight                              |                       | kg        | 19                  | 19                  | 19                  | 19                  |
| <b>Outdoor unit</b>                     |                       |           | <b>CU-Z25UBEA</b>   | <b>CU-Z35UBEA</b>   | <b>CU-Z50UBEA</b>   | <b>CU-Z60UBEA</b>   |
| Power supply                            |                       | V         | 230                 | 230                 | 230                 | 230                 |
| Recommended fuse                        |                       | A         | 16                  | 16                  | 16                  | —                   |
| Connection indoor / outdoor             |                       | mm²       | 4x1,5 ~ 2,5         | 4x1,5 ~ 2,5         | 4x1,5 ~ 2,5         | —                   |
| Air flow                                | Cool / Heat           | m³/min    | 28,7 / 27,2         | 34,3 / 33,5         | 39,7 / 38,6         | 42,6 / 41,5         |
| Sound pressure <sup>5)</sup>            | Cool / Heat (Hi)      | dB(A)     | 46 / 47             | 48 / 48             | 48 / 48             | 49 / 50             |
| Dimension <sup>6)</sup>                 | H x W x D             | mm        | 542 x 780 x 289     | 619 x 824 x 299     | 695 x 875 x 320     | 695 x 875 x 320     |
| Net weight                              |                       | kg        | 33                  | 35                  | 43                  | 43                  |
| Piping diameter                         | Liquid                | Inch (mm) | 1/4 [6,35]          | 1/4 [6,35]          | 1/4 [6,35]          | 1/4 [6,35]          |
|   | Gas                   | Inch (mm) | 3/8 [9,52]          | 3/8 [9,52]          | 1/2 [12,70]         | 1/2 [12,70]         |
| Pipe length range                       |                       | m         | 3 ~ 20              | 3 ~ 20              | 3 ~ 30              | 3 ~ 30              |
| Elevation difference (in / out)         |                       | m         | 15                  | 15                  | 20                  | 20                  |
| Pre-charged pipe length                 |                       | m         | 7,5                 | 7,5                 | 7,5                 | 7,5                 |
| Additional gas amount                   |                       | g/m       | 10                  | 10                  | 15                  | 15                  |
| Refrigerant (R32) / CO <sub>2</sub> Eq. |                       | kg / T    | 0,88 / 0,594        | 0,93 / 0,628        | 1,13 / 0,763        | 1,13 / 0,763        |
| Operating range                         | Cool Min ~ Max        | °C        | -10 ~ +43           | -10 ~ +43           | -10 ~ +43           | -10 ~ +43           |
|   | Heat Min ~ Max        | °C        | -15 ~ +24           | -15 ~ +24           | -15 ~ +24           | -15 ~ +24           |

1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The specification listed on the table indicates values under the condition of 25 Pa [2,5 mmAq] which are applied for factory default setting. Change switch on PCB from Hi to S-Hi to have more than 6,0 mmAq. 5) The sound pressure of the indoor unit shows the value measured of a position of 1,5 m below the unit with 1 m duct on the suction side and 2 m duct on the discharge side. For outdoor unit 1 m in front and 1 m in rear side of main body. The sound pressure is measured in accordance with JIS C 9612. 6) Add 100 mm for indoor unit or 70 mm for outdoor unit for piping port.

## Accessories

**CZ-TACG1** Wi-Fi adapter for smart control via Panasonic Comfort Cloud App

## Accessories

**CZ-CAPRA1** RAC interface adapter for integration into S-Link  
**CZ-RL511D** Optional wireless control kit




SEER and SCOP: For KIT-Z25-UD3. INTERNET CONTROL: Optional.



## Free Multi system

If air conditioning requirements exceed the scope of a single room, Panasonic offers an extensive range of possibilities with a multi split solution.



The multi split solution offers high flexibility, as 2 to 5 indoor units can be connected to a single outdoor unit. The wide range of compatible indoor units includes Etherea and TZ wall-mounted units, floor console, 4 way 60x60 cassette and low static pressure hide-away.

Full flexibility up to 9,0 kW and up to 5 ports with wide range of indoor units including high performance Etherea indoor units, reaching up to A+++ / A++.

### Why a multi split is better than several separate split units

#### Up to 5 indoor units with a single outdoor unit.

- Just one compact outdoor unit
- Increased comfort in the house since every room has its own indoor unit for heating or cooling
- Much more powerful than a single split

- More efficient since the units are always operating at full capacity
- You can connect all types of indoor units, such as wall types and consoles, depending on what suits your house best



#### Solution with single split.

One indoor unit is connected to one outdoor unit. The indoor unit is placed in the main hallway and heats the entire house. Certain rooms may not be perfectly heated, which causes inadequate comfort.

#### Solution with multi split.

With one outdoor unit, you can connect up to five indoor units. There is one indoor unit per room or area. It gives an extreme increase in comfort levels. On the roof, there is only one outdoor unit.

1. Laundry room. 2. Entrance. 3. Kitchen / dining area. 4. Bathroom. 5. Living room. 6. Bedroom.



# Free Multi system

## Outdoor units Free Multi system Z · R32

- Up to 5 indoor units with a single outdoor unit
- Up to 5 rooms with individual control
- Etherea, TZ super-compact, floor console and 4 way 60x60 cassette with nanoe™ X technology to improve protection 24/7
- High energy efficiency class A+++ SEER
- Indoor units compatible with internet and voice control

Configure your multi split system in a few steps using our online tool and see all possible combinations.



| Outdoor unit                            |                  |                 | CU-2Z35TBE   | CU-2Z41TBE   | CU-2Z50TBE   | CU-3Z52TBE   | CU-3Z68TBE    | CU-4Z68TBE    | CU-4Z80TBE    | CU-5Z90TBE    |
|---|------------------|-----------------|--------------|--------------|--------------|--------------|---------------|---------------|---------------|---------------|
| Indoor nominal capacity (Min - Max)     |                  |                 | 3,2 ~ 6,0 kW | 3,2 ~ 6,0 kW | 3,2 ~ 7,7 kW | 4,5 ~ 9,5 kW | 4,5 ~ 11,2 kW | 4,5 ~ 11,5 kW | 4,5 ~ 14,7 kW | 4,5 ~ 18,3 kW |
| Cooling capacity                        | Nominal          | kW              | 3,50         | 4,10         | 5,00         | 5,20         | 6,80          | 6,80          | 8,00          | 9,00          |
|   | Min              |                 | 1,50         | 1,50         | 1,50         | 1,80         | 1,90          | 1,90          | 3,00          | 2,90          |
|   | Max              |                 | 4,50         | 5,20         | 5,40         | 7,30         | 8,00          | 8,80          | 9,20          | 11,50         |
| EER <sup>1)</sup>                       | Nominal          | W/W             | 4,86         | 4,56         | 4,24         | 4,77         | 3,66          | 4,39          | 4,04          | 4,09          |
|   | Min              |                 | 6,00         | 6,00         | 6,00         | —            | 7,04          | 5,59          | 5,66          | 5,27          |
|   | Max              |                 | 4,09         | 3,80         | 3,62         | —            | 3,38          | 3,56          | 3,21          | 2,98          |
| SEER <sup>2)</sup>                      |                  |                 | 8,50 A+++    | 8,50 A+++    | 8,50 A+++    | 8,50 A+++    | 8,00 A++      | 8,00 A++      | 7,90 A++      | 8,50 A+++     |
| Pdesign (cooling)                       |                  | kW              | 3,50         | 4,10         | 5,00         | 5,20         | 6,80          | 6,80          | 8,00          | 9,00          |
| Input power                             | Nominal          | kW              | 0,72         | 0,90         | 1,18         | 1,09         | 1,86          | 1,55          | 1,98          | 2,20          |
|   | Min              |                 | 0,25         | 0,25         | 0,25         | 0,36         | 0,27          | 0,34          | 0,53          | 0,55          |
|   | Max              |                 | 1,10         | 1,37         | 1,49         | 2,18         | 2,37          | 2,47          | 2,87          | 3,86          |
| Annual energy consumption <sup>3)</sup> |                  | kWh/a           | 144          | 169          | 206          | 214          | 298           | 298           | 990           | 1100          |
| Heating capacity                        | Nominal          | kW              | 4,20         | 4,60         | 5,60         | 6,80         | 8,50          | 8,50          | 9,40          | 10,40         |
|   | Min              |                 | 1,10         | 1,10         | 1,10         | 1,60         | 3,30          | 3,00          | 4,20          | 3,40          |
|   | Max              |                 | 5,60         | 7,00         | 7,20         | 8,30         | 10,40         | 10,60         | 10,60         | 14,50         |
| Heating capacity at -7 °C               |                  | kW              | 3,39         | 4,18         | 4,28         | 3,95         | 4,45          | 4,45          | 6,42          | 8,62          |
| COP <sup>1)</sup>                       | Nominal          | W/W             | 4,88         | 4,79         | 4,63         | 4,63         | 3,95          | 4,47          | 4,63          | 4,84          |
|   | Min              |                 | 5,24         | 5,24         | 5,24         | 5,00         | 5,32          | 5,17          | 6,00          | 6,42          |
|   | Max              |                 | 4,18         | 3,91         | 4,00         | 3,82         | 3,64          | 3,96          | 3,46          | 3,42          |
| SCOP <sup>2)</sup>                      |                  |                 | 4,60 A++     | 4,60 A++     | 4,60 A++     | 4,20 A+      | 4,20 A+       | 4,20 A+       | 4,70 A++      | 4,68 A++      |
| Pdesign at -10 °C                       |                  | kW              | 3,20         | 3,50         | 4,20         | 5,00         | 5,20          | 5,80          | 6,80          | 8,50          |
| Input power                             | Nominal          | kW              | 0,86         | 0,96         | 1,21         | 1,47         | 2,15          | 1,90          | 2,03          | 2,15          |
|   | Min              |                 | 0,21         | 0,21         | 0,21         | 0,32         | 0,62          | 0,58          | 0,70          | 0,53          |
|   | Max              |                 | 1,34         | 1,79         | 1,80         | 2,17         | 2,86          | 2,68          | 3,06          | 4,24          |
| Annual energy consumption <sup>3)</sup> |                  | kWh/a           | 974          | 1065         | 1278         | 1667         | 1733          | 1933          | 2026          | 2543          |
| Current                                 | Cool / Heat      | A               | 3,35/4,00    | 4,15/4,45    | 5,35/5,50    | 5,00/6,70    | 8,40/9,70     | 7,00/8,60     | 9,50/9,50     | 10,50/10,10   |
| Power supply                            |                  | V               | 230          | 230          | 230          | 230          | 230           | 230           | 230           | 230           |
| Recommended fuse                        |                  | A               | 16           | 16           | 16           | 16           | 16            | 20            | 20            | 25            |
| Recommended power cable section         |                  | mm <sup>2</sup> | 2,5          | 2,5          | 2,5          | 2,5          | 2,5           | 2,5           | 2,5           | 4,0           |
| Sound pressure <sup>4)</sup>            | Cool / Heat (Hi) | dB(A)           | 48/50        | 48/50        | 50/52        | 47/48        | 51/52         | 49/50         | 51/52         | 53/54         |
| Dimension <sup>5)</sup>                 | H x W x D        | mm              | 619x824x299  | 619x824x299  | 619x824x299  | 795x875x320  | 795x875x320   | 795x875x320   | 999x940x340   | 999x940x340   |
| Net weight                              |                  | kg              | 39           | 39           | 39           | 71           | 71            | 72            | 80            | 81            |
| Piping diameter                         | Liquid           | Inch (mm)       | 1/4 (6,35)   | 1/4 (6,35)   | 1/4 (6,35)   | 1/4 (6,35)   | 1/4 (6,35)    | 1/4 (6,35)    | 1/4 (6,35)    | 1/4 (6,35)    |
|   | Gas              | Inch (mm)       | 3/8 (9,52)   | 3/8 (9,52)   | 3/8 (9,52)   | 3/8 (9,52)   | 3/8 (9,52)    | 3/8 (9,52)    | 3/8 (9,52)    | 3/8 (9,52)    |
| Pipe length range total <sup>6)</sup>   |                  | m               | 6 ~ 30       | 6 ~ 30       | 6 ~ 30       | 6 ~ 50       | 6 ~ 60        | 6 ~ 60        | 6 ~ 70        | 6 ~ 80        |
| Pipe length range to one unit           |                  | m               | 3 ~ 20       | 3 ~ 20       | 3 ~ 20       | 3 ~ 25       | 3 ~ 25        | 3 ~ 25        | 3 ~ 25        | 3 ~ 25        |
| Elevation difference (in / out)         |                  | m               | 10           | 10           | 10           | 15           | 15            | 15            | 15            | 15            |
| Pre-charged pipe length                 |                  | m               | 20           | 20           | 20           | 30           | 30            | 30            | 45            | 45            |
| Additional gas amount                   |                  | g/m             | 15           | 15           | 15           | 20           | 20            | 20            | 20            | 20            |
| Refrigerant (R32) / CO <sub>2</sub> Eq. |                  | kg / T          | 1,12/0,756   | 1,12/0,756   | 1,12/0,756   | 2,10/1,418   | 2,10/1,418    | 2,10/1,418    | 2,72/1,836    | 2,72/1,836    |
| Operating range                         | Cool Min ~ Max   | °C              | -10 ~ +46    | -10 ~ +46    | -10 ~ +46    | -10 ~ +46    | -10 ~ +46     | -10 ~ +46     | -10 ~ +46     | -10 ~ +46     |
|   | Heat Min ~ Max   | °C              | -15 ~ +24    | -15 ~ +24    | -15 ~ +24    | -15 ~ +24    | -15 ~ +24     | -15 ~ +24     | -15 ~ +24     | -15 ~ +24     |

1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the units shows the value measured of a position 1 m in front and 1 m in rear side of the main body. The sound pressure is measured in accordance with JIS C 9612. 5) Add 70 or 95 mm for piping port. 6) Minimum piping length is 3 meters per indoor unit.

## Possible outdoor / indoor units combinations

| Rooms | Outdoor unit | Indoor capacity connected<br>(Min - Max) | Wall-mounted Etherea |    |    |    |    |    |    | Wall-mounted TZ super-compact |    |    |    |    |    |    | Floor console |    |    |    | 4 Way 60x60 cassette |    |    |    |    | Low static pressure hide-away |    |    |    |    |    |
|-------|--------------|--|----------------------|----|----|----|----|----|----|-------------------------------|----|----|----|----|----|----|---------------|----|----|----|----------------------|----|----|----|----|-------------------------------|----|----|----|----|----|
|       |              |  | 16                   | 20 | 25 | 35 | 42 | 50 | 71 | 16                            | 20 | 25 | 35 | 42 | 50 | 60 | 71            | 20 | 25 | 35 | 50                   | 20 | 25 | 35 | 50 | 60                            | 20 | 25 | 35 | 50 | 60 |
| 2     | CU-2Z35TBE   | 3,2~6,0 kW                               | ●                    | ●  | ●  | ●  |    |    |    | ●                             | ●  | ●  | ●  |    |    |    |               | ●  | ●  | ●  |                      | 1) | 1) | 1) |    |                               | ●  | ●  | ●  |    |    |
|       | CU-2Z41TBE   | 3,2~6,0 kW                               | ●                    | ●  | ●  | ●  |    |    |    | ●                             | ●  | ●  | ●  |    |    |    |               | ●  | ●  | ●  |                      | 1) | 1) | 1) |    |                               | ●  | ●  | ●  |    |    |
|       | CU-2Z50TBE   | 3,2~7,7 kW                               | ●                    | ●  | ●  | ●  | 1) | 1) |    | ●                             | ●  | ●  | ●  | 1) | 1) |    |               | ●  | ●  | ●  | 1)                   | 1) | 1) | 1) |    |                               | ●  | ●  | ●  | 1) |    |
| 3     | CU-3Z52TBE   | 4,5~9,5 kW                               | ●                    | ●  | ●  | ●  | 1) | 1) |    | ●                             | ●  | ●  | ●  | 1) | 1) |    |               |    |    |    | ●                    | 1) | 1) | 1) | 1) |                               | ●  | ●  | ●  | 1) |    |
|       | CU-3Z68TBE   | 4,5~11,2 kW                              | ●                    | ●  | ●  | ●  | 1) | 1) |    | ●                             | ●  | ●  | ●  | 1) | 1) | 1) |               |    |    |    | ●                    | 1) | 1) | 1) | 1) | 2)                            | ●  | ●  | ●  | 1) | 1) |
| 4     | CU-4Z68TBE   | 4,5~11,5 kW                              | ●                    | ●  | ●  | ●  | 1) | 1) |    | ●                             | ●  | ●  | ●  | 1) | 1) | 1) |               |    |    |    | ●                    | 1) | 1) | 1) | 1) | 2)                            | ●  | ●  | ●  | 1) | 1) |
|       | CU-4Z80TBE   | 4,5~14,7 kW                              | ●                    | ●  | ●  | ●  | 1) | 1) | 3) | ●                             | ●  | ●  | ●  | 1) | 1) | 1) | 3)            |    |    |    | ●                    | 1) | 1) | 1) | 1) | 2)                            | ●  | ●  | ●  | 1) | 1) |
| 5     | CU-5Z90TBE   | 4,5~18,3 kW                              | ●                    | ●  | ●  | ●  | 1) | 1) | 3) | ●                             | ●  | ●  | ●  | 1) | 1) | 1) | 3)            |    |    |    | ●                    | 1) | 1) | 1) | 1) | 2)                            | ●  | ●  | ●  | 1) | 1) |

1) Pipe reducer CZ-MA1PA required. 2) Pipe reducer CZ-MA2PA required. 3) Pipe reducers CZ-MA2PA and CZ-MA3PA required.






Optional wired remote controller.  
CZ-RD517C

INTERNET CONTROL: Built-in Wi-Fi.



| Wall-mounted Etherea | Indoor unit graphite grey | Indoor unit silver | Indoor unit matt white | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure <sup>1)</sup> |  | Dimension / Net weight | Piping diameter      |
|----------------------|---------------------------|--------------------|------------------------|------------------|------------------|-----------------------|------------------------------|--|------------------------|----------------------|
|                      |                           |                    |                        | kW               | kW               |                       | Cool — Heat (Hi/Lo/S-Lo)     |  |                        |                      |
|                      |                           |                    |                        |                  |                  |                       |                              |  | H x W x D              | Liquid / Gas         |
|                      |                           |                    |                        |                  |                  |                       |                              |  | mm / kg                | Inch (mm)            |
| 1,6 kW               | —                         | —                  | CS-MZ16ZKE             | 1,60             | 2,60             | 4x1,5                 | 38/26/21 — 39/27/21          |  | 295x870x229/10         | 1/4(6,35)/3/8(9,52)  |
| 2,0 kW               | CS-XZ20ZKEW-H             | CS-XZ20ZKEW        | CS-Z20ZKEW             | 2,00             | 3,20             | 4x1,5                 | 39/26/21 — 40/27/21          |  | 295x870x229/10         | 1/4(6,35)/3/8(9,52)  |
| 2,5 kW               | CS-XZ25ZKEW-H             | CS-XZ25ZKEW        | CS-Z25ZKEW             | 2,50             | 3,60             | 4x1,5                 | 41/27/21 — 43/29/21          |  | 295x870x229/10         | 1/4(6,35)/3/8(9,52)  |
| 3,5 kW <sup>2)</sup> | CS-XZ35ZKEW-H             | CS-XZ35ZKEW        | CS-Z35ZKEW             | 3,50             | 4,50             | 4x1,5                 | 44/30/21 — 45/35/21          |  | 295x870x229/11         | 1/4(6,35)/3/8(9,52)  |
| 4,2 kW <sup>3)</sup> | CS-XZ42ZKEW-H             | —                  | CS-Z42ZKEW             | 4,20             | 5,60             | 4x1,5                 | 44/33/27 — 45/37/31          |  | 295x870x229/10         | 1/4(6,35)/1/2(12,70) |
| 5,0 kW <sup>4)</sup> | —                         | CS-XZ50ZKEW        | CS-Z50ZKEW             | 5,00             | 6,80             | 4x2,5                 | 44/39/32 — 46/39/32          |  | 295x1040x244/12        | 1/4(6,35)/1/2(12,70) |
| 7,1 kW               | —                         | —                  | CS-Z71ZKEW             | 7,10             | 8,70             | 4x2,5                 | 49/40/32 — 49/40/32          |  | 295x1040x244/13        | 1/4(6,35)/5/8(15,88) |



Optional wired remote controller.  
CZ-RD517C

INTERNET CONTROL: Built-in Wi-Fi.



| Wall-mounted TZ super-compact | Indoor unit | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure <sup>1)</sup> |  | Dimension / Net weight | Piping diameter      |
|-------------------------------|-------------|------------------|------------------|-----------------------|------------------------------|--|------------------------|----------------------|
|                               |             | kW               | kW               |                       | Cool — Heat (Hi/Lo/S-Lo)     |  |                        |                      |
|                               |             |                  |                  |                       |                              |  | H x W x D              | Liquid / Gas         |
|                               |             |                  |                  |                       |                              |  | mm / kg                | Inch (mm)            |
| 1,6 kW                        | CS-MTZ16ZKE | 1,60             | 2,60             | 4x1,5                 | 38/27/22 — 39/28/24          |  | 290x779x209/8          | 1/4(6,35)/3/8(9,52)  |
| 2,0 kW                        | CS-TZ20ZKEW | 2,00             | 3,20             | 4x1,5                 | 37/25/20 — 38/26/22          |  | 290x779x209/8          | 1/4(6,35)/3/8(9,52)  |
| 2,5 kW                        | CS-TZ25ZKEW | 2,50             | 3,60             | 4x1,5                 | 40/26/20 — 40/27/22          |  | 290x779x209/8          | 1/4(6,35)/3/8(9,52)  |
| 3,5 kW <sup>2)</sup>          | CS-TZ35ZKEW | 3,50             | 4,50             | 4x1,5                 | 42/30/20 — 42/33/22          |  | 290x779x209/8          | 1/4(6,35)/3/8(9,52)  |
| 4,2 kW                        | CS-TZ42ZKEW | 4,20             | 5,60             | 4x1,5                 | 44/31/29 — 44/35/34          |  | 290x779x209/8          | 1/4(6,35)/1/2(12,70) |
| 5,0 kW                        | CS-TZ50ZKEW | 5,00             | 6,80             | 4x2,5                 | 44/37/33 — 44/37/33          |  | 290x779x209/8          | 1/4(6,35)/1/2(12,70) |
| 6,0 kW                        | CS-TZ60ZKEW | 6,00             | 8,50             | 4x2,5                 | 45/37/34 — 45/37/34          |  | 295x1040x244/12        | 1/4(6,35)/1/2(12,70) |
| 7,1 kW                        | CS-TZ71ZKEW | 7,10             | 8,70             | 4x2,5                 | 47/38/35 — 47/38/35          |  | 295x1040x244/13        | 1/4(6,35)/5/8(15,88) |




Optional wired remote controller.  
CZ-RD517C

INTERNET CONTROL: Optional.



| Floor console <sup>5)</sup> | Indoor unit | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure <sup>6)</sup> |  | Dimension / Net weight | Piping diameter      |
|-----------------------------|-------------|------------------|------------------|-----------------------|------------------------------|--|------------------------|----------------------|
|                             |             | kW               | kW               |                       | Cool — Heat (Hi/Lo/S-Lo)     |  |                        |                      |
|                             |             |                  |                  |                       |                              |  | H x W x D              | Liquid / Gas         |
|                             |             |                  |                  |                       |                              |  | mm / kg                | Inch (mm)            |
| 2,0 kW                      | CS-MZ20UFEA | 2,00             | 3,20             | 4x1,5                 | 39/27/22 — 39/27/21          |  | 600x750x207/13         | 1/4(6,35)/3/8(9,52)  |
| 2,5 kW                      | CS-Z25UFEAW | 2,50             | 3,60             | 4x1,5                 | 40/27/22 — 40/27/21          |  | 600x750x207/13         | 1/4(6,35)/3/8(9,52)  |
| 3,5 kW <sup>2)</sup>        | CS-Z35UFEAW | 3,50             | 4,50             | 4x1,5                 | 41/28/22 — 41/28/21          |  | 600x750x207/13         | 1/4(6,35)/3/8(9,52)  |
| 5,0 kW                      | CS-Z50UFEAW | 5,00             | 5,30             | 4x1,5                 | 44/33/29 — 48/35/31          |  | 600x750x207/13         | 1/4(6,35)/1/2(12,70) |



Optional wired remote controller.  
CZ-RT6W or CZ-RTC6

Panel (sold separately).  
CZ-KPY4

INTERNET CONTROL and BMS CONNECTIVITY: Optional.



| 4 Way 60x60 cassette* | Indoor unit (Panel CZ-KPY4) | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure <sup>7)</sup> |  | Dimension / Net weight |                 | Piping diameter      |
|-----------------------|-----------------------------|------------------|------------------|-----------------------|------------------------------|--|------------------------|-----------------|----------------------|
|                       |                             | kW               | kW               |                       | Cool — Heat (Hi/Lo/S-Lo)     |  | Indoor H x W x D       | Panel H x W x D |                      |
|                       |                             |                  |                  |                       |                              |  | mm / kg                | mm / kg         | Liquid / Gas         |
|                       |                             |                  |                  |                       |                              |  |                        |                 | Inch (mm)            |
| 2,0 kW                | S-M20PY3E                   | 2,00             | 3,20             | 4x1,5                 | 33/30/27 — 33/30/27          |  | 243x575x575/15         | 30x625x625/2,8  | 1/4(6,35)/1/2(12,70) |
| 2,5 kW                | S-25PY3E                    | 2,50             | 3,60             | 4x1,5                 | 33/30/27 — 33/30/27          |  | 243x575x575/15         | 30x625x625/2,8  | 1/4(6,35)/1/2(12,70) |
| 3,5 kW <sup>2)</sup>  | S-36PY3E                    | 3,50             | 3,60             | 4x1,5                 | 36/32/27 — 36/32/27          |  | 243x575x575/15         | 30x625x625/2,8  | 1/4(6,35)/1/2(12,70) |
| 5,0 kW <sup>4)</sup>  | S-50PY3E                    | 5,00             | 6,80             | 4x1,5                 | 41/36/29 — 41/36/29          |  | 243x575x575/15         | 30x625x625/2,8  | 1/4(6,35)/1/2(12,70) |
| 6,0 kW                | S-60PY3E                    | 6,00             | 8,50             | 4x1,5                 | 45/39/33 — 45/39/33          |  | 243x575x575/15         | 30x625x625/2,8  | 3/8(9,52)/5/8(15,88) |

\* Compatible with Commercial control and connectivity accessories only. For detailed information go to the control systems section.



Optional wireless control kit.  
CZ-RL511D

INTERNET CONTROL and BMS CONNECTIVITY: Optional.



| Low static pressure hide-away | Indoor unit  | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure <sup>8)</sup> |  | Dimension / Net weight | Piping diameter      |
|-------------------------------|--------------|------------------|------------------|-----------------------|------------------------------|--|------------------------|----------------------|
|                               |              | kW               | kW               |                       | Cool — Heat (Hi/Lo/S-Lo)     |  |                        |                      |
|                               |              |                  |                  |                       |                              |  | H x W x D              | Liquid / Gas         |
|                               |              |                  |                  |                       |                              |  | mm / kg                | Inch (mm)            |
| 2,0 kW                        | CS-MZ20UD3EA | 2,00             | 3,20             | 4x1,5                 | 34/29/26 — 36/29/26          |  | 200x750x640/19         | 1/4(6,35)/3/8(9,52)  |
| 2,5 kW                        | CS-Z25UD3EAW | 2,50             | 3,60             | 4x1,5                 | 35/29/26 — 37/29/26          |  | 200x750x640/19         | 1/4(6,35)/3/8(9,52)  |
| 3,5 kW <sup>2)</sup>          | CS-Z35UD3EAW | 3,50             | 4,50             | 4x1,5                 | 35/29/26 — 37/29/26          |  | 200x750x640/19         | 1/4(6,35)/3/8(9,52)  |
| 5,0 kW <sup>4)</sup>          | CS-Z50UD3EAW | 5,00             | 6,80             | 4x1,5                 | 41/31/28 — 41/32/29          |  | 200x750x640/19         | 1/4(6,35)/1/2(12,70) |
| 6,0 kW                        | CS-Z60UD3EAW | 6,00             | 8,50             | 4x1,5                 | 43/32/29 — 43/34/31          |  | 200x750x640/19         | 1/4(6,35)/1/2(12,70) |

1) The sound pressure of the indoor unit shows the value measured at a position of 1 m in front of the main body and 0,8 m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 2) Heating capacity in combination with Free Multi outdoor units except with CU-Z235TBE. In this case, the heating capacity is 4,20 kW. 3) Heating capacity in combination with Free Multi outdoor units except with CU-Z250TBE. In this case, the heating capacity is 5,00 kW. 4) Heating capacity in combination with Free Multi outdoor units except with CU-Z235TBE. In this case, the heating capacity is 5,30 kW. 5) Compatible only with 2 ports R32 outdoor CU-Z235TBE / CU-Z241TBE / CU-Z250TBE. Minimum quantity of connection: 2 indoor units. 6) The sound pressure of the units shows the value measured at a position 1 m in front of the main body and 1 m above floor. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 7) The sound pressure of the indoor unit shows the value measured at a position of 1,5 m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 8) The sound pressure of the indoor unit shows the value measured at a position of 1,5 m below the unit with 1 m duct on the suction side and 2 m duct on the discharge side. The sound pressure is measured in accordance with JIS C 9612.



# Multi TZ system

## Outdoor units Multi TZ · R32

- Up to 3 indoor units with a single outdoor unit
- Up to 3 rooms with individual control
- High energy efficiency class A++ SEER
- Flexible installation, compact units and large connection distance
- Indoor units compatible with internet and voice control



| Outdoor unit                            |                     |           | CU-2TZ41TBE        | CU-2TZ50TBE        | CU-3TZ52TBE        |
|---|---------------------|-----------|--------------------|--------------------|--------------------|
| Indoor nominal capacity (Min - Max)     |                     |           | 3,2 ~ 6,0 kW       | 3,2 ~ 7,7 kW       | 4,5 ~ 9,5 kW       |
| Cooling capacity                        | Nominal (Min - Max) | kW        | 4,10 [1,50 - 4,70] | 5,00 [1,50 - 5,40] | 5,20 [1,80 - 6,60] |
| EER <sup>1)</sup>                       | Nominal (Min - Max) | W/W       | 4,14 [5,56 - 3,41] | 3,85 [5,56 - 3,33] | 4,52 [3,67 - 5,00] |
| SEER <sup>2)</sup>                      |                     |           | 7,10 A++           | 7,00 A++           | 7,60 A++           |
| Pdesign (cooling)                       |                     | kW        | 4,10               | 5,00               | 5,20               |
| Input power                             | Nominal (Min - Max) | kW        | 0,99 [0,27 - 1,38] | 1,30 [0,27 - 1,62] | 1,15 [0,36 - 1,80] |
| Annual energy consumption <sup>3)</sup> |                     | kWh/a     | 202                | 250                | 239                |
| Heating capacity                        | Nominal (Min - Max) | kW        | 4,40 [1,10 - 6,30] | 5,70 [1,10 - 6,40] | 6,80 [1,60 - 7,50] |
| Heating capacity at -7 °C               |                     | kW        | 3,75               | 3,80               | —                  |
| COP <sup>1)</sup>                       | Nominal (Min - Max) | W/W       | 4,44 [5,00 - 3,54] | 4,35 [5,00 - 3,62] | 4,28 [3,87 - 5,00] |
| SCOP <sup>2)</sup>                      |                     |           | 4,30 A+            | 4,20 A+            | 4,20 A+            |
| Pdesign at -10 °C                       |                     | kW        | 3,50               | 4,50               | 5,00               |
| Input power                             | Nominal (Min - Max) | kW        | 0,99 [0,22 - 1,78] | 1,31 [0,22 - 1,77] | 1,59 [0,32 - 1,94] |
| Annual energy consumption <sup>3)</sup> |                     | kWh/a     | 1139               | 1500               | 1667               |
| Current                                 | Cool / Heat         | A         | 4,60 / 4,60        | 6,00 / 6,00        | 5,30 / 7,30        |
| Power supply                            |                     | V         | 230                | 230                | 230                |
| Sound pressure <sup>4)</sup>            | Cool / Heat (Hi)    | dB(A)     | 48 / 50            | 50 / 52            | 48 / 48            |
| Dimension <sup>5)</sup>                 | H x W x D           | mm        | 542 x 780 x 289    | 542 x 780 x 289    | 795 x 875 x 320    |
| Net weight                              |                     | kg        | 35                 | 35                 | 71                 |
| Piping diameter                         | Liquid              | Inch (mm) | 1/4 [6,35]         | 1/4 [6,35]         | 1/4 [6,35]         |
|   | Gas                 | Inch (mm) | 3/8 [9,52]         | 3/8 [9,52]         | 3/8 [9,52]         |
| Pipe length range total                 |                     | m         | 6 ~ 30             | 6 ~ 30             | 6 ~ 50             |
| Pipe length range to one unit           |                     | m         | 3 ~ 20             | 3 ~ 20             | 3 ~ 25             |
| Elevation difference (in / out)         |                     | m         | 10                 | 10                 | 15                 |
| Pre-charged pipe length                 |                     | m         | 20                 | 20                 | 30                 |
| Additional gas amount                   |                     | g/m       | 15                 | 15                 | 20                 |
| Refrigerant (R32) / CO <sub>2</sub> Eq. |                     | kg / T    | 0,9 / 0,6075       | 0,9 / 0,6075       | 2,1 / 1,4175       |
| Operating range                         | Cool Min ~ Max      | °C        | -10 ~ +46          | -10 ~ +46          | -10 ~ +46          |
|   | Heat Min ~ Max      | °C        | -15 ~ +24          | -15 ~ +24          | -15 ~ +24          |

1) EER and COP calculation is based in accordance to EN14511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the units shows the value measured of a position 1 m in front and 1 m in rear side of the main body. The sound pressure is measured in accordance with JIS C 9612. 5) Add 70 or 95 mm for piping port.



## Possible outdoor / indoor units combinations

| Rooms | Outdoor unit | Indoor capacity connected (Min - Max) | Wall-mounted TZ super-compact |    |    |    |    |    |
|-------|--------------|---------------------------------------|-------------------------------|----|----|----|----|----|
|       |              |                                       | 16                            | 20 | 25 | 35 | 42 | 50 |
| 2     | CU-2TZ41TBE  | 3,2 ~ 6,0 kW                          | ✓                             | ✓  | ✓  | ✓  |    |    |
|       | CU-2TZ50TBE  | 3,2 ~ 7,7 kW                          | ✓                             | ✓  | ✓  | ✓  | ✓  | ✓  |
| 3     | CU-3TZ52TBE  | 4,5 ~ 9,5 kW                          | ✓                             | ✓  | ✓  | ✓  | ✓  | ✓  |

Minimum quantity of connection: 2 indoor units.



Optional wired remote controller.  
CZ-RD517C














INTERNET CONTROL: Built-in Wi-Fi.



| Wall-mounted TZ super-compact | Indoor unit | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure <sup>1)</sup>      | Dimension / Net weight | Piping diameter           |
|-------------------------------|-------------|------------------|------------------|-----------------------|-----------------------------------|------------------------|---------------------------|
|                               |             | kW               | kW               | mm <sup>2</sup>       | Cool — Heat (Hi/Lo/S-Lo)<br>dB(A) | H x W x D<br>mm / kg   | Liquid / Gas<br>Inch (mm) |
| 1,6 kW                        | CS-MTZ16ZKE | 1,60             | 2,60             | 4x1,5                 | 38 / 27 / 22 — 39 / 28 / 24       | 290 x 779 x 209 / 8    | 1/4 [6,35] / 3/8 [9,52]   |
| 2,0 kW                        | CS-TZ20ZKEW | 2,00             | 3,20             | 4x1,5                 | 37 / 25 / 20 — 38 / 26 / 22       | 290 x 779 x 209 / 8    | 1/4 [6,35] / 3/8 [9,52]   |
| 2,5 kW                        | CS-TZ25ZKEW | 2,50             | 3,60             | 4x1,5                 | 40 / 26 / 20 — 40 / 27 / 22       | 290 x 779 x 209 / 8    | 1/4 [6,35] / 3/8 [9,52]   |
| 3,5 kW                        | CS-TZ35ZKEW | 3,50             | 4,50             | 4x1,5                 | 42 / 30 / 20 — 42 / 33 / 22       | 290 x 779 x 209 / 8    | 1/4 [6,35] / 3/8 [9,52]   |
| 4,2 kW                        | CS-TZ42ZKEW | 4,20             | 5,60             | 4x1,5                 | 44 / 31 / 29 — 44 / 35 / 34       | 290 x 779 x 209 / 8    | 1/4 [6,35] / 1/2 [12,70]  |
| 5,0 kW                        | CS-TZ50ZKEW | 5,00             | 6,80             | 4x2,5                 | 44 / 37 / 33 — 44 / 37 / 33       | 290 x 779 x 209 / 8    | 1/4 [6,35] / 1/2 [12,70]  |






































1) The sound pressure of the indoor unit shows the value measured of a position of 1 m in front of the main body and 0,8 m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed.

# Compare solutions

|  | Indoor unit dimension   | Efficiency <sup>1)</sup> | Indoor air quality  | Outdoor temperature  | Comfort         | Super Quiet  | Connectivity            |
|--|---|--------------------------|---|--|-----------------|--|-------------------------|
| <b>Wall-mounted Etherea -</b><br><b>2,0 to 7,1 kW</b>          | <br>295<br>x<br>870<br>x<br>229<br>(295 x 1040 x 244 wide model) | <b>A+++</b><br>A+++      | <br>nanoe X Generator Mark 3   | <b>-10 °C</b><br>in cooling mode<br><b>-20 °C</b><br>in heating mode | Aerowings 2.0   | <br><b>19 dB(A)</b>   | <b>Built-in Wi-Fi</b>   |
| <b>Wall-mounted TZ super-compact -</b><br><b>2,0 to 7,1 kW</b> | <br>290<br>x<br>779<br>x<br>209<br>(295 x 1040 x 244 wide model) | <b>A++</b><br>A++        | <br>nanoe X Generator Mark 1   | <b>-10 °C</b><br>in cooling mode<br><b>-15 °C</b><br>in heating mode | Aerowings       | <br><b>20 dB(A)</b>   | <b>Built-in Wi-Fi</b>   |
| <b>Wall-mounted BZ super-compact -</b><br><b>2,5 to 6,0 kW</b> | <br>290<br>x<br>779<br>x<br>209                                 | <b>A++</b><br>A+         | PM2,5 Filter  | <b>-10 °C</b><br>in cooling mode<br><b>-15 °C</b><br>in heating mode | Aerowings       | <br><b>20 dB(A)</b>   | Optional Wi-Fi CZ-TACG1 |
| <b>Floor console -</b><br><b>2,5 to 5,0 kW</b>                 | <br>600<br>x<br>750<br>x<br>207                                | <b>A++</b><br>A++        | <br>nanoe X Generator Mark 1 | <b>-10 °C</b><br>in cooling mode<br><b>-15 °C</b><br>in heating mode | Double air flow | <br><b>20 dB(A)</b> | Optional Wi-Fi CZ-TACG1 |
| <b>Low static pressure hide-away -</b><br><b>2,5 to 6,0 kW</b> | <br>200<br>x<br>750<br>x<br>640                                | <b>A+</b><br>A+          | Air filter  | <b>-10 °C</b><br>in cooling mode<br><b>-15 °C</b><br>in heating mode | Weekly timer    | <br><b>24 dB(A)</b> | Optional Wi-Fi CZ-TACG1 |

<sup>1)</sup> Energy efficiency class in 2,5 kW references. \* All data in this chart is applicable in most of the models in each line up, check product specifications to confirm.

# Feature comparison

| Models  | Wall-mounted<br>Etherea · R32            | Wall-mounted TZ<br>super-compact · R32    |
|---|--|---|
|  Refrigerant R32                                     | ✓  | ✓   |
|  Econavi. Sunlight sensor                            |  |   |
|  Inverter+ system                                    | ✓  |   |
|  Inverter system                                     |  | ✓   |
|  R2 rotary compressor                                | ✓  | ✓   |
|  nanoe X Generator                                   | ✓ Mark 3                                 | ✓ Mark 1                                  |
|  PM2,5 Filter  |  |   |
|  Dust collection filter                              |  |   |
|  Antiallergy properties                              | ✓  | ✓   |
|  Super Quiet <sup>1)</sup>                           | ✓ 19 dB(A) for XZ/Z20, XZ/Z25 and XZ/Z35 | ✓ 20 dB(A) for TZ20, TZ25 and TZ35        |
|  Inside cleaning                                     | ✓  |   |
|  Mild Dry cooling                                    | ✓  |   |
|  Aerowings   | ✓  | ✓   |
|  Down to -10 °C in cooling only                      | ✓  | ✓   |
|  Down to -15 °C in heating mode                     | ✓ -20 °C                                 | ✓   |
|  Summer House                                      |  |   |
|  R410A/R22 Renewal                                 | ✓  | ✓   |
|  Odour-removing function                           | ✓  | ✓   |
|  Removable, washable panel                         | ✓  | ✓   |
|  Powerful mode                                     | ✓  | ✓   |
|  Soft dry operation mode                           | ✓  | ✓   |
|  Personal air flow creation                        | ✓  | ✓ For TZ60 and TZ71                       |
|  Automatic vertical air flow control               |  | ✓ For TZ20, TZ25, TZ35, TZ42 and TZ50     |
|  Manual horizontal air flow control                |  | ✓ For TZ20, TZ25, TZ35, TZ42 and TZ50     |
|  Auto mode   | ✓  | ✓   |
|  Hot start mode                                    | ✓  | ✓   |
|  Real time clock with dual ON / OFF timer          | ✓  | ✓   |
|  Weekly timer                                      |  |   |
|  LCD infrared remote controller                    | ✓  | ✓   |
|  Automatic restart                                 | ✓  | ✓   |
|  Long piping                                       | ✓ 15 m,<br>30 m (XZ/Z50, Z71)            | ✓ 15 m, 20 m (TZ50), 30 m (TZ71 and TZ60) |
|  Top-Panel maintenance access                      | ✓  | ✓   |
|  Self-diagnosis function                           | ✓  | ✓   |
|  RAC interface adapter for integration into S-Link | ✓  | ✓   |
|  Wi-Fi control                                     | ✓ Built-in                               | ✓ Built-in                                |
|  Easy control by BMS                               | ✓  | ✓   |
|  Warranty on the compressor                        | ✓  | ✓   |

1) At the lowest fan speed. 2) Tested by 3rd party laboratory, SP, according to EN14511:2013 and SP Method 1721, this temperature is not guaranteed by Factory.





| Wall-mounted BZ<br>super-compact · R32 | Floor console<br>· R32     | Low static pressure<br>hide-away · R32 |
|--|----------------------------|--|
| ✓                                      | ✓                          | ✓                                      |
|  | ✓                          |  |
| ✓                                      |                            | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
|  | ✓ Mark 1                   |  |
| ✓                                      |                            |  |
|  | ✓                          |  |
| ✓ 20 dB(A) for BZ25 and BZ35           | ✓ 20 dB(A) for Z25 and Z35 |  |
|  |                            |  |
| ✓                                      |                            |  |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
|  |                            |  |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          |  |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
|  |                            |  |
| ✓                                      | ✓                          |  |
| ✓                                      | ✓                          |  |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          |  |
|  |                            | ✓                                      |
| ✓                                      | ✓                          |  |
| ✓                                      | ✓                          | ✓                                      |
| ✓ 15 m, 30 m (BZ60)                    | ✓ 20 m, 30 m (Z50)         | ✓ 20 m, 30 m (Z50 and Z60)             |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |
| ✓                                      | ✓                          | ✓                                      |

# Features explained

## Energy saving



### Refrigerant R32.

Our heat pumps containing R32 refrigerant show a drastic reduction in the value of Global Warming Potential (GWP). An important step to reduce greenhouse gases. R32 is also a component refrigerant, making it easy to recycle.



### Econavi. Sunlight sensor.

Sunlight Sensor technology can detect and reduce the waste of energy by optimising air conditioner operation according to room conditions. With just one touch of a button, you can save energy.



### Inverter Plus system.

Inverter Plus system classification highlights Panasonic's highest performing systems.



### Inverter.

The Inverter range provides greater efficiency and comfort. Provides more precise temperature control, without highs and lows, and keeps the ambient temperature constant with lower energy consumption and a significant reduction in noise and vibration levels.



### Panasonic R2 rotary compressor.

Designed to withstand extreme conditions, it delivers high performance and efficiency.

## High performance and indoor air quality



### nanoe™ X.

Technology with the benefits of hydroxyl radicals has the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise.



### PM2.5 filter.

This filter can capture airborne particulate matter (PM2.5), including hazardous pollutants, as well as house dust and pollen.



### Dust collection filter.

This filter collects and retains particles suspended in the air, resulting in cleaner air in the room.



### Antiallergy properties.

System is equipped with antiallergy properties filter.



### Inside cleaning.

This function works to dry the inside of the indoor unit with nanoe™ X. It can inhibit certain adhered bacteria, viruses and mould with up to 99% efficiency.



### Super Quiet.

Thanks to its latest generation compressor and its twin blade fan, our outdoor unit is one of the most silent on the market. The indoor unit emits an almost imperceptible 18 dB(A).



### Mild Dry cooling.

Fine control helps prevent a rapid decrease in room humidity while maintaining the set temperature. Maintains an RH\* up to 10% higher than cooling operation (\*RH: Relative Humidity). Ideal when sleeping with the air conditioner on.



### Aerowings.

Panasonic's Aerowings feature incorporates two blades that concentrate the airflow to cool or heat in the shortest possible time by distributing the air evenly throughout the room.



### Down to -10 °C in cooling mode.

The air conditioner works in cooling mode when the outdoor temperature of -10 °C.



### Down to -15 °C in heating mode.

The air conditioner works in heat pump mode when the outdoor temperature is as low as -15 °C.



### Summer House.

This innovative function keeps the house at 8/10 or 8/15 °C to avoid freezing pipes during the winter. This function is beneficial for summer or weekend homes.



### R22/R410A Renewal.

The Panasonic renewal system allows good quality existing R410A or R22 pipe work to be re-used whilst installing high efficiency R32 systems.



### Odour-removing function.

Allows the exchanger to be cleaned, preventing possible odours. While this function is connected, the fan also remains OFF momentarily to avoid unpleasant odours while the exchanger is being cleaned.



### Removable, washable panel.

The front panel is easy to keep clean. It can be removed quickly in one single step and can be washed in water. A clean front panel ensures smoother, more efficient operation, which can save energy.



### Powerful mode.

The rapid and effective powerful mode is ideal for when you come home on the hottest or coldest days. It works at maximum power to reach the desired temperature in just 15 minutes.



### Soft Dry operation mode.

The soft dry mode eliminates excess moisture with a soft breeze and provides a sense of wellbeing without much change in temperature.



### Personal air flow creation.

Permits the air direction to be adjusted vertically and horizontally. This feature can be conveniently selected by remote controller.



### Automatic vertical air flow control.

The flap swings up and down automatically. The flow can also be set at a fixed angle with the remote controller.



### Manual horizontal air flow control.



### Auto mode.

Automatically switches the current operation mode to heating or cooling mode necessary to keep the temperature at a constantly comfortable level based on the temperature of the room. In case of multi split installation the function is limited to first unit working and logic of switching is different considering also the outdoor temperature.



### Hot Start mode.

At the start of heating cycle and after defrost cycle, the indoor fan will start up once the indoor heat exchanger is warm.



### Real time clock with dual ON / OFF timer.

This feature enables you to preset two different sets of start/stop operation timer (hour and minute) within a 24-hour time frame.



### Weekly timer.

Allow to fix per each day of the week up to 6 operations per day.



### LCD infrared remote controller.



### Automatic restart.

This function permits automatic restarting if safe mode operation has stopped for some unusual reason, such as after a power cut. As soon as the power is back, the unit restarts with the parameters selected before it stopped.



### Long piping.

Indicates the maximum length of pipe between the outdoor unit and the indoor unit(s). The distances permitted, demonstrate the installations possible.



### Top-panel maintenance access.

Maintenance of an outdoor unit used to be quite a tedious task. Now, with the possibility of removing the top cover, maintenance is quick and easy.



### Self-diagnosis function.

With this function the unit carries out a process self-diagnosis when a particular function does not work correctly. This allows faster servicing.

## High connectivity



### Domestic integration to S-Link - CZ-CAPRA1.

Can connect RAC range to S-Link. Full control is now possible.



### Wi-Fi control.

The Panasonic Comfort Cloud App allows users to conveniently manage and monitor Panasonic residential heat pumps from a mobile device, anytime, anywhere.



### BMS connectivity.

The communication port can be integrated into the indoor unit and provides easy connection to, and control of, your Panasonic air conditioner to your home or Building Management System.












### 5 Years compressor warranty.





We guarantee the outdoor unit compressors in the entire range for five years.

# Accessories and control

## Connectivity





|  |  |   |
|--|--|---|
|  <p><b>Wi-Fi adapter for smart control via Panasonic Comfort Cloud App.</b></p> <p>-----<br/>CZ-TACG1</p>                               |  <p><b>Interface adapter for integration into S-Link, plus external input and alarm/status output.</b></p> <p>-----<br/>CZ-CAPRA1</p>   |  <p><b>KNX interface. Can be used with all models which have a CN-CNT connector (Intesis).</b></p> <p>-----<br/>PAW-AC-KNX-1i</p>  |
|  <p><b>Modbus interface. Can be used with all models which have a CN-CNT connector (Intesis).</b></p> <p>-----<br/>PAW-AC-MBS-1</p>     |  <p><b>BACnet interface. Can be used with all models which have a CN-CNT connector (Intesis).</b></p> <p>-----<br/>PAW-AC-BAC-1</p>     |  <p><b>KNX interface. Can be used with all models which have a CN-CNT connector (Airzone).</b></p> <p>-----<br/>PAW-AZAC-KNX-1</p> |
|  <p><b>Modbus interface. Can be used with all models which have a CN-CNT connector (Airzone).</b></p> <p>-----<br/>PAW-AZAC-MBS-1</p> |  <p><b>BACnet interface. Can be used with all models which have a CN-CNT connector (Airzone).</b></p> <p>-----<br/>PAW-AZAC-BAC-1</p> |  <p><b>This interface can be used with all models which have a CN-RMT connector.</b></p> <p>-----<br/>PAW-AC-DIO</p>             |

## Individual controls

|  |  |  |  |
|--|--|--|--|
|  <p><b>Wired remote controller for wall-mounted and floor console.</b></p> <p>-----<br/>CZ-RD517C</p> |  <p><b>Infrared remote controller Sky Remote. 2 m cable length of infrared receiver for hide-away.</b></p> <p>-----<br/>CZ-RL511D</p> |  <p><b>CONEX wired remote controller (non-wireless) for 4 way 60x60 cassette - PY3, white.</b></p> <p>-----<br/>CZ-RTC6W</p> |  <p><b>CONEX wired remote controller (non-wireless) for 4 way 60x60 cassette - PY3, black.</b></p> <p>-----<br/>CZ-RTC6</p> |
|--|--|--|--|

## Panel

## Pipe reducer

|  |  |  |  |
|--|--|--|--|
|  <p><b>Panel for 4 way 60x60 cassette - PY3.</b></p> <p>-----<br/>CZ-KPY4</p> |  <p><b>Reduces the connection size on the indoor unit from 1/2" to 3/8".</b></p> <p>-----<br/>CZ-MA1PA</p> |  <p><b>Increases the connection size on the outdoor unit from 3/8" to 1/2".</b></p> <p>-----<br/>CZ-MA2PA</p> |  <p><b>Reduces the connection size on the indoor unit from 5/8" to 1/2".</b></p> <p>-----<br/>CZ-MA3PA</p> |
|--|--|--|--|




# Dimensions



## Domestic

|   |       |
|---|-------|
| Heatcharge VZ   | → 470 |
| Etherea   | → 471 |
| TZ super-compact  | → 473 |
| BZ super-compact  | → 475 |
| UZ super-compact  | → 476 |
| Floor console   | → 477 |
| Low static pressure hide-away                             | → 478 |
| Indoor unit Free Multi system Z -<br>4 Way 60x60 cassette | → 479 |
| Outdoor units Free Multi System Z                         | → 480 |
| Outdoor units Multi Wall TZ                               | → 481 |

## Wall-mounted Heatcharge VZ.




## Relative position between the indoor unit and the installation plate




Unit: mm

# Wall-mounted Etherea (from 1,6 to 4,2 kW).


Side view




Front view




Side view




Bottom view




Rear view




## Relative position between the indoor unit and the installation plate




Top view




Side view



Front view



Side view




2-way valve at liquid side (high pressure)


3-way valve at gas side (low pressure)

## Wall-mounted Etherea (5,0 and 7,1 kW).


Side view




Front view




Side view




Bottom view




Rear view




Relative position between the indoor unit and the installation plate




Top view




Side view



Front view



Side view




2-way valve at liquid side (high pressure)


3-way valve at gas side (low pressure)



# Wall-mounted TZ super-compact (from 1,6 to 5,0 kW).




## Relative position between the indoor unit and the installation plate




## CU-TZ20ZKE / CU-TZ25ZKE / CU-TZ35ZKE / CU-TZ42ZKE

### Top view




### Front view




2-way valve at liquid side (high pressure)  
3-way valve at gas side (low pressure)

### Side view




### Side view



## CU-TZ50ZKE

### Top view




### Front view



2-way valve at liquid side (high pressure)  
3-way valve at gas side (low pressure)


### Side view




Unit: mm

## Wall-mounted TZ super-compact (6,0 and 7,1 kW).


Side view




Front view




Side view




Bottom view



Rear view




Relative position between the indoor unit and the installation plate




CU-TZ60ZKE

Top view



CU-TZ71ZKE


Top view



Side view


Front view

Side view




Side view

Front view




Side view




Unit: mm

# Wall-mounted BZ super-compact.


Side view




Front view




Side view




Bottom view



Rear view




Relative position between the indoor unit and the installation plate




CU-BZ25ZKE / CU-BZ35ZKE

Top view




Front view

Side view




CU-BZ50ZKE

Top view




Front view

Side view




CU-BZ60ZKE

Top view



Front view


Side view




Unit: mm

## Wall-mounted UZ super-compact.


Side view




Front view




Side view




Bottom view



Rear view




Relative position between the indoor unit and the installation plate




CU-UZ25ZKE / CU-UZ35ZKE

Top view



CU-UZ50ZKE

Top view



Side view


Front view

Side view

Side view

Front view


Side view



Unit: mm




Floor console.




CU-Z25UBEA

Top view




Front view

Side view




CU-Z35UBEA

Top view




Front view

Side view




CU-Z50UBEA

Top view




Front view

Side view




Unit: mm

Low static pressure hide-away.




CU-Z25UBEA

Top view




Front view

Side view




CU-Z35UBEA

Top view




Front view

Side view




CU-Z50UBEA / CU-Z60UBEA

Top view




Front view

Side view



Unit: mm

# Indoor unit Free Multi system Z - 4 Way 60x60 cassette.




\* Length of supplied drain piping= 250 mm.

| Type  | 20-50           | 60              |
|---|-----------------|-----------------|
| 1 Air inlet   |                 |                 |
| 2 Air outlet  |                 |                 |
| 3 Refrigerant piping (liquid)                               | Ø6,35 (flared)  | Ø9,52 (flared)  |
| 4 Refrigerant piping (gas)                                  | Ø12,70 (flared) | Ø15,88 (flared) |
| 5 Drain piping connection port VP20                         |                 |                 |
| 6 Power supply port   |                 |                 |
| 7 Suspension bolt hole [4-11x26 slot]                       |                 |                 |
| 8 Fresh air inlet duct connection port [Ø100] <sup>1)</sup> |                 |                 |

1) Necessary to attach duct connecting flange (field supply).


Filter dimension: 362 x 362 x 15 mm.




Detailed view X

## Outdoor units Free Multi System Z.


CU-2Z35TBE / CU-2Z41TBE / CU-2Z50TBE



CU-3Z52TBE / CU-3Z68TBE / CU-4Z68TBE



CU-4Z80TBE / CU-5Z90TBE




Unit: mm




## Outdoor units Multi Wall TZ.

### CU-2TZ41TBE / CU-2TZ50TBE



### CU-3TZ52TBE



# Wiring diagrams

## Domestic

|  |       |
|--|-------|
| Wall-mounted kits 1x1                  | → 529 |
| Floor console kits 1x1                 | → 530 |
| Low static pressure hide-away kits 1x1 | → 530 |
| Free Multi System 2 rooms              | → 531 |
| Free Multi System 3 rooms              | → 531 |
| Free Multi System 4 rooms              | → 532 |
| Free Multi System 5 rooms              | → 532 |

## Wall-mounted kits 1x1.

Indoor unit



Outdoor unit




Attention: Wall-mounted Etherea and TZ super-compact have different connection terminals



Single phase  
Power supply  
230 V / 50 Hz



Infrared remote  
controller (included  
in the delivery)



Optional wired  
remote controller

Power supply to indoor or outdoor depending on model, see table.

### Wall-mounted Heatcharge VZ - R32

| Indoor unit | Power supply   | Recommended fuse | Connection indoor / outdoor | Outdoor unit |
|-------------|----------------|------------------|-----------------------------|--------------|
| CS-VZ9SKE   | 230 V (indoor) | 16 A             | 4 x 1,5 mm <sup>2</sup>     | CU-VZ9SKE    |
| CS-VZ12SKE  | 230 V (indoor) | 16 A             | 4 x 1,5 mm <sup>2</sup>     | CU-VZ12SKE   |

### Wall-mounted Etherea Graphite grey, Silver and Matt white - R32

| Indoor unit                              | Power supply   | Recommended fuse | Power supply cable      | Connection indoor / outdoor | Outdoor unit |
|--|----------------|------------------|-------------------------|-----------------------------|--------------|
| CS-XZ20ZKEW-H / CS-XZ20ZKEW / CS-Z20ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z20ZKE    |
| CS-XZ25ZKEW-H / CS-XZ25ZKEW / CS-Z25ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z25ZKE    |
| CS-XZ35ZKEW-H / CS-XZ35ZKEW / CS-Z35ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z35ZKE    |
| CS-XZ42ZKEW-H / — / CS-Z42ZKEW           | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z42ZKE    |
| — / CS-XZ50ZKEW / CS-Z50ZKEW             | 230 V (indoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-Z50ZKE    |
| — / — / CS-Z71ZKEW                       | 230 V (indoor) | 20 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-Z71ZKE    |

### Wall-mounted TZ super-compact - R32

| Indoor unit | Power supply   | Recommended fuse | Power supply cable      | Connection indoor / outdoor | Outdoor unit |
|-------------|----------------|------------------|-------------------------|-----------------------------|--------------|
| CS-TZ20ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-TZ20ZKE   |
| CS-TZ25ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-TZ25ZKE   |
| CS-TZ35ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-TZ35ZKE   |
| CS-TZ42ZKEW | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-TZ42ZKE   |
| CS-TZ50ZKEW | 230 V (indoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-TZ50ZKE   |
| CS-TZ60ZKEW | 230 V (indoor) | 20 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-TZ60ZKE   |
| CS-TZ71ZKEW | 230 V (indoor) | 20 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-TZ71ZKE   |

### Wall-mounted BZ super-compact - R32


| Indoor unit | Power supply   | Recommended fuse | Power supply cable      | Connection indoor / outdoor | Outdoor unit |
|-------------|----------------|------------------|-------------------------|-----------------------------|--------------|
| CS-BZ25ZKE  | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-BZ25ZKE   |
| CS-BZ35ZKE  | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-BZ35ZKE   |
| CS-BZ50ZKE  | 230 V (indoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-BZ50ZKE   |
| CS-BZ60ZKE  | 230 V (indoor) | 20 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-BZ60ZKE   |

### Wall-mounted UZ super-compact - R32

| Indoor unit | Power supply   | Recommended fuse | Power supply cable      | Connection indoor / outdoor | Outdoor unit |
|-------------|----------------|------------------|-------------------------|-----------------------------|--------------|
| CS-UZ25WKE  | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-UZ25WKE   |
| CS-UZ35WKE  | 230 V (indoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-UZ35WKE   |
| CS-UZ50WKE  | 230 V (indoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-UZ50WKE   |

Floor console kits 1x1.

Indoor unit



Outdoor unit






Single phase  
Power supply  
230 V / 50 Hz

Floor console - R32

| Indoor unit | Power supply    | Recommended fuse | Power supply cable      | Connection indoor / outdoor | Outdoor unit |
|-------------|-----------------|------------------|-------------------------|-----------------------------|--------------|
| CS-Z25UFEAW | 230 V (outdoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z25UBEA   |
| CS-Z35UFEAW | 230 V (outdoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z35UBEA   |
| CS-Z50UFEAW | 230 V (outdoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 2,5 mm <sup>2</sup>     | CU-Z50UBEA   |

Low static pressure hide-away kits 1x1.

Indoor unit



Outdoor unit



Single phase  
Power supply  
230 V / 50 Hz



Low static pressure hide-away kits - R32

| Indoor unit  | Power supply    | Recommended fuse | Power supply cable      | Connection indoor / outdoor | Outdoor unit |
|--------------|-----------------|------------------|-------------------------|-----------------------------|--------------|
| CS-Z25UD3EAW | 230 V (outdoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z25UBEA   |
| CS-Z35UD3EAW | 230 V (outdoor) | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z35UBEA   |
| CS-Z50UD3EAW | 230 V (outdoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z50UBEA   |
| CS-Z60UD3EAW | 230 V (outdoor) | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     | CU-Z60UBEA   |



## Free Multi System 2 rooms.

Indoor unit



Outdoor unit




Single phase  
Power supply  
230 V / 50 Hz / 16 A

## Free Multi System - R32

| Outdoor unit | Power supply | Recommended fuse | Power supply cable      | Connection indoor / outdoor |
|--------------|--------------|------------------|-------------------------|-----------------------------|
| CU-2Z35TBE   | 230 V        | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-2Z41TBE   | 230 V        | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-2Z50TBE   | 230 V        | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-2TZ41TBE  | 230 V        | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-2TZ50TBE  | 230 V        | 16 A             | 3 x 1,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |

## Free Multi System 3 rooms.

Indoor unit



Outdoor unit




Single phase  
Power supply  
230 V / 50 Hz / 16 A

## Free Multi System - R32

| Outdoor unit | Power supply | Recommended fuse | Power supply cable      | Connection indoor / outdoor |
|--------------|--------------|------------------|-------------------------|-----------------------------|
| CU-3Z52TBE   | 230 V        | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-3Z68TBE   | 230 V        | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-3TZ52TBE  | 230 V        | 16 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |

Free Multi System 4 rooms.

Indoor unit



Attention: Wall-mounted Etherea and TZ super-compact have different connection terminals (Multi Split)

Outdoor unit




Single phase  
Power supply  
230 V / 50 Hz / 20 A

Free Multi System · R32

| Outdoor unit | Power supply | Recommended fuse | Power supply cable      | Connection indoor / outdoor |
|--------------|--------------|------------------|-------------------------|-----------------------------|
| CU-4Z68TBE   | 230 V        | 20 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |
| CU-4Z80TBE   | 230 V        | 20 A             | 3 x 2,5 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |

Free Multi System 5 rooms.

Indoor unit



Attention: Wall-mounted Etherea and TZ super-compact have different connection terminals (Multi Split)

Outdoor unit



Single phase  
Power supply  
230 V / 50 Hz / 25 A

Free Multi System · R32

| Outdoor unit | Power supply | Recommended fuse | Power supply cable      | Connection indoor / outdoor |
|--------------|--------------|------------------|-------------------------|-----------------------------|
| CU-5Z90TBE   | 230 V        | 25 A             | 3 x 4,0 mm <sup>2</sup> | 4 x 1,5 mm <sup>2</sup>     |

## Panasonic service

Our Panasonic Service teams are committed to ensuring your peace of mind. Best service is our aim.

Panasonic provides a team of highly trained technicians and engineers to deliver professional and responsive services that meet the highest levels of quality and safety while being efficient and cost effective.

To find out more about Panasonic Heating & Cooling Solutions, please visit **[www.aircon.panasonic.be](http://www.aircon.panasonic.be)**.



### Maintenance.

To meet the requirements of the standard warranty, the product must be maintained and serviced annually by a suitably trained and qualified engineer. This way we can extend the lifetime of the product.



### Repair.

Panasonic offers a wide range of service agreements, like Panasonic Service+ for a maximized product lifetime. Leave the care of your Panasonic products to the experts. In the unlikely event that something goes wrong, trust one of our qualified and Panasonic trained experts to get things back on track.




### Warranty.

In accordance with the regulations, Panasonic guarantees its products against hidden defects. Moreover, Panasonic grants to the professional purchaser a commercial warranty, specific to the product families, subject to compliance of all the rules of installation and use of its products.

## Panasonic Heating & Cooling Solutions customer service

Panasonic enables different channels for end users or professionals to get in touch with us:



Use our European website **[www.aircon.panasonic.be](http://www.aircon.panasonic.be)** for contacting us.

Panasonic has implemented a contact page on the Panasonic Heating & Cooling Solutions website for potential or existing Panasonic customers.



Another option is to contact the highly experienced teams at the Panasonic customer service center, who are more than qualified to support Panasonic clients in 13 different languages across Europe.

### Our service center in Europe for end customers:

| Country    | B2C support center | Opening times |
|------------|--------------------|---------------|
| Belgium NL | +32 2 320 55 38    | Mo-Fr 9-17h   |
| Belgium FR | +32 2 320 55 38    | Mo-Fr 9-17h   |
| Luxemburg  | +32 2 320 55 38    | Mo-Fr 9-17h   |

**Panasonic Marketing Europe GmbH**  
**Panasonic Heating & Ventilation Air-Conditioning Europe**  
Hagenauer Strasse 43, 65203 Wiesbaden, Germany  
**[www.aircon.panasonic.be](http://www.aircon.panasonic.be)**

**France / Belgium / Luxembourg**  
**Panasonic Solutions Chauffage & Refroidissement**  
1 à 7 Rue du 19 Mars 1962, 92238, Gennevilliers  
Cedex, France  
☎ 0800 805 215 (France)  
+32 2 320 55 38 (Belgium & Luxembourg)  
**[www.aircon.panasonic.be](http://www.aircon.panasonic.be)**

**Panasonic®**

To find out how Panasonic cares for you,  
log on to: **[www.aircon.panasonic.be](http://www.aircon.panasonic.be)**

**Panasonic Belgium**  
**Branch of Panasonic Marketing Europe GmbH**  
**Heating & Cooling Solutions - Business location**  
Dok Noord 3A/404  
9000 Gent

**Panasonic Belgium**  
**Branch of Panasonic Marketing Europe GmbH**  
**Registered Office**  
Brusselsesteenweg 159  
9090 Melle



Do not add or replace refrigerant other than the specified type. Manufacturer is not responsible for the damage and deterioration in safety due to usage of the other refrigerant.  
The outdoor units in this catalogue contains fluorinated greenhouse gases with a GWP higher than 150.

